

# PETERBILT REGIONAL HAUL TRUCKS 337

## PACCAR PX-8 (2010-2013)



**ENGINE** Paccar PX-8  
Capacity: 22,7-23,7 liter

USE	CLIMATE
Refuse truck, mixer, dump truck: average speed > 25 mph	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Armado Synth LSP Ultra 5W-30</b>	<b>Armado Synth LSP Ultra 10W-40</b>	<b>Armado Synth MSP 5W-40</b>

*Change every 12000 miles/ 6 months/ 500 hours*

USE	CLIMATE
Refuse truck, mixer, dump truck: average speed 20 - 25 mph	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Armado Synth LSP Ultra 5W-30</b>	<b>Armado Synth LSP Ultra 10W-40</b>	<b>Armado Synth MSP 5W-40</b>

*Change every 9000 miles/ 6 months/ 500 hours*

USE	CLIMATE
Refuse truck, mixer, dump truck: average speed 15 - 20 mph	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Armado Synth LSP Ultra 5W-30</b>	<b>Armado Synth LSP Ultra 10W-40</b>	<b>Armado Synth MSP 5W-40</b>

*Change every 8500 miles/ 6 months/ 500 hours*

USE	CLIMATE
Refuse truck, mixer, dump truck: average speed 10 - 15 mph	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Armado Synth LSP Ultra 5W-30</b>	<b>Armado Synth LSP Ultra 10W-40</b>	<b>Armado Synth MSP 5W-40</b>

*Change every 6000 miles/ 6 months/ 500 hours*

USE	CLIMATE
Refuse truck, mixer, dump truck: average speed < 10 mph	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Armado Synth LSP Ultra 5W-30</b>	<b>Armado Synth LSP Ultra 10W-40</b>	<b>Armado Synth MSP 5W-40</b>

*Change every 3000 miles/ 6 months/ 500 hours*

USE	CLIMATE
Fuel economy > 7 MPG and GVW < 60000 lbs	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Armado Synth LSP Ultra 5W-30</b>	<b>Armado Synth LSP Ultra 10W-40</b>	<b>Armado Synth MSP 5W-40</b>

*Change every 15000 miles/ 6 months/ 500 hours*

USE	CLIMATE
Fuel economy < 7 MPG or dusty areas or idle time > 40% or gvw > 60000 lbs	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Armado Synth LSP Ultra 5W-30</b>	<b>Armado Synth LSP Ultra 10W-40</b>	<b>Armado Synth MSP 5W-40</b>

*Change every 9000 miles/ 6 months/ 500 hours*

# PETERBILT REGIONAL HAUL TRUCKS 337

## PACCAR PX-8 (2010-2013)

**DIFFERENTIAL** Eaton/Dana

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**SP Gear 1011**

PRODUCT RECOMMENDATION 2

**Syngear TDL 75W-90***Check every 15000 miles, change every 50000 miles***TRANSMISSION AUTOMATIC** Allison

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 2032***Check every 15000 miles, change every 25000 miles***TRANSMISSION MANUAL** Fuller

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Multifleet SCD 50***Check every 15000 miles, change every 50000 miles***POWER STEERING**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**ATF Dexron II-D***Check every 7500 miles, change every 60000 miles/ 6 months*

# PETERBILT REGIONAL HAUL TRUCKS 337

## PACCAR PX-8 (2010-2013)



### COOLING SYSTEM

Capacity: 12,4 liter (Engine only)

USE		CLIMATE
On-road use		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

Change every 750000 miles/ 72 months/ 22000 hours

USE		CLIMATE
Off-road use		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

Change every 96 months/ 15000 hours

### SELECTIVE CATHALYTIC REDUCTION SYSTEM (SCR)

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*