

RENAULT (EU) K SERIES EURO 6 K 380 (4X4) EURO 6 (2014-2022)



ENGINE DTi 11
Capacity: 36,5 liter

USE	CLIMATE
Long distance, predominantly flat, max 90km/h, =<44t	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30

Change every 100000 km/ 12 months

USE	CLIMATE
Long distance, hilly, =<44t	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30

Change every 75000 km/ 12 months

USE	CLIMATE
Long distance, predominantly flat, 45-70t	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30

Change every 60000 km/ 12 months/ 750 hours

USE	CLIMATE
Long distance, hilly, 45-70t	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30

Change every 45000 km/ 12 months/ 600 hours

USE	CLIMATE
Long distance, predominantly flat, 71-80t	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30

Change every 45000 km/ 12 months/ 600 hours

USE	CLIMATE
Long distance, hilly, 71-80t, fuel =<120 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30

Change every 20000 km/ 12 months/ 600 hours

USE	CLIMATE
Long distance, >80t, fuel =<120 L/100km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30

Change every 20000 km/ 12 months/ 600 hours

RENAULT (EU) K SERIES EURO 6 K 380 (4X4) EURO 6 (2014-2022)



USE		CLIMATE
Regional, 33-44t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	

Change every 60000 km/ 12 months/ 750 hours

USE		CLIMATE
Regional, 45-70t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	

Change every 45000 km/ 12 months/ 600 hours

USE		CLIMATE
Distribution, city =<32t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	

Change every 45000 km/ 12 months/ 600 hours

USE		CLIMATE
Regional, =<32t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	

Change every 75000 km/ 12 months

DIFFERENTIAL FRONT FAA11		
USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90

Check every 10000 km

USE		CLIMATE
All conditions		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90

Change every 120000 km/ 24 months

DIFFERENTIAL REAR P 1361.6/7		
Capacity: 18-20 liter, Capacity: 2 liter (each hub)		

RENAULT (EU) K SERIES EURO 6 K 380 (4X4) EURO 6 (2014-2022)



USE		CLIMATE
Construction Site, extended, hilly, 45-80t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 200000 km/ 36 months</i>		
USE		CLIMATE
Construction Site, hilly, 45-80t		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 85W-140		
<i>Change every 60000 km/ 12 months</i>		
USE		CLIMATE
All other conditions (alternative)		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 85W-140		
<i>Change every 120000 km/ 12 months</i>		
USE		CLIMATE
All other conditions (preferred)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 450000 km/ 36 months</i>		
USE		CLIMATE
Construction Site, very hilly, >80t		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 85W-140		
<i>Change every 600 hours</i>		
USE		CLIMATE
Construction Site, extended, very hilly, >80t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 2500 hours</i>		

RETARDER RET-TH

Capacity: 5,4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

RENAULT (EU) K SERIES EURO 6 K 380 (4X4) EURO 6 (2014-2022)



TRANSFERBOX Volvo VT2501TB
Capacity: 5,5 liter

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear MT/LD 75W-80	Syngear TDL 75W-90

Check every 10000 km

USE		CLIMATE
All conditions		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear MT/LD 75W-80	Syngear TDL 75W-90

Change every 180000 km/ 12 months

TRANSMISSION MANUAL Volvo VT2214B 14/2
Capacity: 13 liter, Capacity: 14 liter (+ PTO)

USE		CLIMATE
Long distance, hilly, 71-80t, fuel =<120 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 200000 km/ 36 months

USE		CLIMATE
Long distance, alternative, hilly, 71-80t		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		

Change every 200000 km/ 36 months

USE		CLIMATE
All other conditions		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 450000 km/ 36 months

USE		CLIMATE
All other conditions (alternative)		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		

Change every 450000 km/ 36 months

RENAULT (EU) K SERIES EURO 6 K 380 (4X4) EURO 6 (2014-2022)



TRANSMISSION SEMI-AUTOMATIC Optidriver, AT 2412E (Volvo I-Shift) 12/3
Capacity: 14,5 liter, Capacity: 15,5 liter (+ PTO)

USE		CLIMATE
All other conditions		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 200000 km/ 36 months

USE		CLIMATE
All other conditions (alternative)		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		

Change every 200000 km/ 36 months

USE		CLIMATE
Construction Site, very hilly, >80t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 2500 hours

HYDRAULIC CAB TILT SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Perlus H 15		

HYDRAULIC CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

RENAULT (EU) K SERIES EURO 6 K 380 (4X4) EURO 6 (2014-2022)

**POWER STEERING**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

COOLING SYSTEM

Capacity: 33,5 liter, Capacity: 46,5 liter (+ retarder)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.