

# RENAULT (EU) K SERIES EURO 6 K 460 (4X4) EURO 6 (2014 AND AFTER)



**ENGINE** DTi 11  
Capacity: 36,5 liter

| USE                                                  | CLIMATE  |
|------------------------------------------------------|----------|
| Long distance, predominantly flat, max 90km/h, =<44t | Moderate |

| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2      |
|-------------------------------------|-------------------------------|
| <b>Dieselfleet LSP Ultra 10W-30</b> | <b>Dieselfleet MSP 10W-30</b> |

Change every 100000 km/ 12 months

| USE                         | CLIMATE  |
|-----------------------------|----------|
| Long distance, hilly, =<44t | Moderate |

| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2      |
|-------------------------------------|-------------------------------|
| <b>Dieselfleet LSP Ultra 10W-30</b> | <b>Dieselfleet MSP 10W-30</b> |

Change every 75000 km/ 12 months

| USE                                       | CLIMATE  |
|-------------------------------------------|----------|
| Long distance, predominantly flat, 45-70t | Moderate |

| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2      |
|-------------------------------------|-------------------------------|
| <b>Dieselfleet LSP Ultra 10W-30</b> | <b>Dieselfleet MSP 10W-30</b> |

Change every 60000 km/ 12 months/ 750 hours

| USE                          | CLIMATE  |
|------------------------------|----------|
| Long distance, hilly, 45-70t | Moderate |

| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2      |
|-------------------------------------|-------------------------------|
| <b>Dieselfleet LSP Ultra 10W-30</b> | <b>Dieselfleet MSP 10W-30</b> |

Change every 45000 km/ 12 months/ 600 hours

| USE                                       | CLIMATE  |
|-------------------------------------------|----------|
| Long distance, predominantly flat, 71-80t | Moderate |

| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2      |
|-------------------------------------|-------------------------------|
| <b>Dieselfleet LSP Ultra 10W-30</b> | <b>Dieselfleet MSP 10W-30</b> |

Change every 45000 km/ 12 months/ 600 hours

| USE                                               | CLIMATE  |
|---------------------------------------------------|----------|
| Long distance, hilly, 71-80t, fuel =<120 L/100 km | Moderate |

| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2      |
|-------------------------------------|-------------------------------|
| <b>Dieselfleet LSP Ultra 10W-30</b> | <b>Dieselfleet MSP 10W-30</b> |

Change every 20000 km/ 12 months/ 600 hours

| USE                                     | CLIMATE  |
|-----------------------------------------|----------|
| Long distance, >80t, fuel =<120 L/100km | Moderate |

| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2      |
|-------------------------------------|-------------------------------|
| <b>Dieselfleet LSP Ultra 10W-30</b> | <b>Dieselfleet MSP 10W-30</b> |

Change every 20000 km/ 12 months/ 600 hours

# RENAULT (EU) K SERIES EURO 6 K 460 (4X4) EURO 6 (2014 AND AFTER)



| USE                                 |                               | CLIMATE  |
|-------------------------------------|-------------------------------|----------|
| Regional, 33-44t                    |                               | Moderate |
| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2      |          |
| <b>Dieselfleet LSP Ultra 10W-30</b> | <b>Dieselfleet MSP 10W-30</b> |          |

Change every 60000 km/ 12 months/ 750 hours

| USE                                 |                               | CLIMATE  |
|-------------------------------------|-------------------------------|----------|
| Regional, 45-70t                    |                               | Moderate |
| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2      |          |
| <b>Dieselfleet LSP Ultra 10W-30</b> | <b>Dieselfleet MSP 10W-30</b> |          |

Change every 45000 km/ 12 months/ 600 hours

| USE                                 |                               | CLIMATE  |
|-------------------------------------|-------------------------------|----------|
| Distribution, city =<32t            |                               | Moderate |
| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2      |          |
| <b>Dieselfleet LSP Ultra 10W-30</b> | <b>Dieselfleet MSP 10W-30</b> |          |

Change every 45000 km/ 12 months/ 600 hours

| USE                                 |                               | CLIMATE  |
|-------------------------------------|-------------------------------|----------|
| Regional, =<32t                     |                               | Moderate |
| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2      |          |
| <b>Dieselfleet LSP Ultra 10W-30</b> | <b>Dieselfleet MSP 10W-30</b> |          |

Change every 75000 km/ 12 months

| DIFFERENTIAL FRONT FAA11 |                           |                                    |
|--------------------------|---------------------------|------------------------------------|
| USE                      |                           | CLIMATE                            |
| First change only        |                           | Moderate                           |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3           |
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |

Check every 10000 km

| USE                      |                           | CLIMATE                            |
|--------------------------|---------------------------|------------------------------------|
| All conditions           |                           | Moderate                           |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3           |
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |

Change every 120000 km/ 24 months

| DIFFERENTIAL REAR P 1361.6/7                        |  |  |
|-----------------------------------------------------|--|--|
| Capacity: 18-20 liter, Capacity: 2 liter (each hub) |  |  |

# RENAULT (EU) K SERIES EURO 6 K 460 (4X4) EURO 6 (2014 AND AFTER)



| USE                                           |                           | CLIMATE  |
|-----------------------------------------------|---------------------------|----------|
| Construction Site, extended, hilly, 45-80t    |                           | Moderate |
| PRODUCT RECOMMENDATION 1                      | PRODUCT RECOMMENDATION 2  |          |
| <b>SP Gear 1011</b>                           | <b>Syngear TDL 75W-90</b> |          |
| <i>Change every 200000 km/ 36 months</i>      |                           |          |
| USE                                           |                           | CLIMATE  |
| Construction Site, hilly, 45-80t              |                           | Moderate |
| PRODUCT RECOMMENDATION 1                      |                           |          |
| <b>Gearlube GL-5 85W-140</b>                  |                           |          |
| <i>Change every 60000 km/ 12 months</i>       |                           |          |
| USE                                           |                           | CLIMATE  |
| All other conditions (alternative)            |                           | Moderate |
| PRODUCT RECOMMENDATION 1                      |                           |          |
| <b>Gearlube GL-5 85W-140</b>                  |                           |          |
| <i>Change every 120000 km/ 12 months</i>      |                           |          |
| USE                                           |                           | CLIMATE  |
| All other conditions (preferred)              |                           | Moderate |
| PRODUCT RECOMMENDATION 1                      | PRODUCT RECOMMENDATION 2  |          |
| <b>SP Gear 1011</b>                           | <b>Syngear TDL 75W-90</b> |          |
| <i>Change every 450000 km/ 36 months</i>      |                           |          |
| USE                                           |                           | CLIMATE  |
| Construction Site, very hilly, >80t           |                           | Moderate |
| PRODUCT RECOMMENDATION 1                      |                           |          |
| <b>Gearlube GL-5 85W-140</b>                  |                           |          |
| <i>Change every 600 hours</i>                 |                           |          |
| USE                                           |                           | CLIMATE  |
| Construction Site, extended, very hilly, >80t |                           | Moderate |
| PRODUCT RECOMMENDATION 1                      | PRODUCT RECOMMENDATION 2  |          |
| <b>SP Gear 1011</b>                           | <b>Syngear TDL 75W-90</b> |          |
| <i>Change every 2500 hours</i>                |                           |          |

## RETARDER RET-TH

Capacity: 5,4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

# RENAULT (EU) K SERIES EURO 6 K 460 (4X4) EURO 6 (2014 AND AFTER)



**TRANSFERBOX** Volvo VT2501TB  
Capacity: 5,5 liter

| USE                      |                             | CLIMATE                   |
|--------------------------|-----------------------------|---------------------------|
| First change only        |                             | Moderate                  |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3  |
| <b>SP Gear 1011</b>      | <b>Syngear MT/LD 75W-80</b> | <b>Syngear TDL 75W-90</b> |

Check every 10000 km

| USE                      |                             | CLIMATE                   |
|--------------------------|-----------------------------|---------------------------|
| All conditions           |                             | Moderate                  |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3  |
| <b>SP Gear 1011</b>      | <b>Syngear MT/LD 75W-80</b> | <b>Syngear TDL 75W-90</b> |

Change every 180000 km/ 12 months

**TRANSMISSION MANUAL** Volvo VT2214B 14/2  
Capacity: 13 liter, Capacity: 14 liter (+ PTO)

| USE                                               |                           | CLIMATE  |
|---------------------------------------------------|---------------------------|----------|
| Long distance, hilly, 71-80t, fuel =<120 L/100 km |                           | Moderate |
| PRODUCT RECOMMENDATION 1                          | PRODUCT RECOMMENDATION 2  |          |
| <b>SP Gear 1011</b>                               | <b>Syngear TDL 75W-90</b> |          |

Change every 200000 km/ 36 months

| USE                                       |  | CLIMATE  |
|-------------------------------------------|--|----------|
| Long distance, alternative, hilly, 71-80t |  | Moderate |
| PRODUCT RECOMMENDATION 1                  |  |          |
| <b>Syngear MT/LD 75W-80</b>               |  |          |

Change every 200000 km/ 36 months

| USE                      |                           | CLIMATE  |
|--------------------------|---------------------------|----------|
| All other conditions     |                           | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  |          |
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> |          |

Change every 450000 km/ 36 months

| USE                                |  | CLIMATE  |
|------------------------------------|--|----------|
| All other conditions (alternative) |  | Moderate |
| PRODUCT RECOMMENDATION 1           |  |          |
| <b>Syngear MT/LD 75W-80</b>        |  |          |

Change every 450000 km/ 36 months

# RENAULT (EU) K SERIES EURO 6 K 460 (4X4) EURO 6 (2014 AND AFTER)



**TRANSMISSION SEMI-AUTOMATIC** Optidriver, AT 2412E (Volvo I-Shift) 12/3  
Capacity: 14,5 liter, Capacity: 15,5 liter (+ PTO)

| USE                      |                           | CLIMATE  |
|--------------------------|---------------------------|----------|
| All other conditions     |                           | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  |          |
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> |          |

*Change every 200000 km/ 36 months*

| USE                                |  | CLIMATE  |
|------------------------------------|--|----------|
| All other conditions (alternative) |  | Moderate |
| PRODUCT RECOMMENDATION 1           |  |          |
| <b>Syngear MT/LD 75W-80</b>        |  |          |

*Change every 200000 km/ 36 months*

| USE                                 |                           | CLIMATE  |
|-------------------------------------|---------------------------|----------|
| Construction Site, very hilly, >80t |                           | Moderate |
| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2  |          |
| <b>SP Gear 1011</b>                 | <b>Syngear TDL 75W-90</b> |          |

*Change every 2500 hours*

| HYDRAULIC CAB TILT SYSTEM |                          |          |
|---------------------------|--------------------------|----------|
| USE                       |                          | CLIMATE  |
| Normal                    |                          | Moderate |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 |          |
| <b>SP Matic 2032</b>      | <b>ATF Almirol</b>       |          |

| USE                      |  | CLIMATE |
|--------------------------|--|---------|
| Normal                   |  | Arctic  |
| PRODUCT RECOMMENDATION 1 |  |         |
| <b>Perlus H 15</b>       |  |         |

| HYDRAULIC CLUTCH SYSTEM          |                           |          |
|----------------------------------|---------------------------|----------|
| USE                              |                           | CLIMATE  |
| Normal                           |                           | Moderate |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  |          |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |          |

# RENAULT (EU) K SERIES EURO 6 K 460 (4X4) EURO 6 (2014 AND AFTER)

**POWER STEERING**

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>SP Matic 2032</b>     | <b>ATF Almirol</b>       |          |

**COOLING SYSTEM**

Capacity: 45 liter, Capacity: 58 liter (+ retarder)

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*