RENAULT (EU) KERAX KERAX 380 DXI EURO 5 (4X2) (2010-2014)



| ENGINE DXi 11 Capacity: 36,5 liter | | | |
|---------------------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal (alternative) | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Armado Synth 5W-30 | Dieselfleet MSP 10W-30 | | |
| Change every 80000 km/ 12 month | 18 | | |

| USE | | CLIMATE | |
|------------------------------|--------------------------|----------|--|
| Normal (preferred) | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Dieselfleet LSP Ultra 10W-30 | Dieselfleet MSP 10W-30 | | |

Change every 100000 km/ 12 months

| DIFFERENTIAL REAR P 1361.6/7 Capacity: 18 liter, Capacity: 2,5 liter (each hub) | | |
|---|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |

Syngear TDL 75W-90

Change every 400000 km/36 months

| 01 0000001 101 | | · |
|--------------------------|--------------------------|----------|
| SP Gear 1011 | Syngear TDL 75W-90 | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Severe | | Moderate |
| USE | | CLIMATE |

Change every 200000 km/24 months

POWER TAKE OFF Capacity: 1 liter

SP Gear 1011

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION MANUAL ZF 16S-1830 16/2 Capacity: 10,4 liter, Capacity: 15 liter (+ intarder)

We are unable to give a standard recommendation for this component. Please contact our service department.

RENAULT (EU) KERAX KERAX 380 DXI EURO 5 (4X2) (2010-2014)



| TRANSMISSION SEMI-AUTOMATIC Option Capacity: 14,5 liter | tidriver+ AT 2612TD (Volvo I-Shift) 12/3 | |
|---|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 40 | | |
| Change every 120000 km/ 24 months | | |
| USE | | CLIMATE |
| Normal (preferred) | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Syngear MT/LD 75W-80 | | |
| Change every 400000 km/ 36 months | | |
| | | · |

| POWER STEERING Capacity: 4,5 liter | | | |
|------------------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| SP Matic 2032 | ATF Almirol | | |

| COOLING SYSTEM | |
|-----------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Coolant SP 16 | |
| Change every 400000 km/ 36 months | ' |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.