

# RENAULT (EU) KERAX KERAX 460 DXI

## EURO 5 (4X2) (2010-2014)



**ENGINE DXi 11**  
Capacity: 36,5 liter

USE	CLIMATE
Normal (alternative)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Armado Synth 5W-30</b>	<b>Dieselfleet MSP 10W-30</b>

*Change every 80000 km/ 12 months*

USE	CLIMATE
Normal (preferred)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Dieselfleet LSP Ultra 10W-30</b>	<b>Dieselfleet MSP 10W-30</b>

*Change every 100000 km/ 12 months*

**DIFFERENTIAL REAR P 1361.6/7**  
Capacity: 18 liter, Capacity: 2,5 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>SP Gear 1011</b>	<b>Syngear TDL 75W-90</b>

*Change every 400000 km/ 36 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>SP Gear 1011</b>	<b>Syngear TDL 75W-90</b>

*Change every 200000 km/ 24 months*

**POWER TAKE OFF**  
Capacity: 1 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

**TRANSMISSION MANUAL ZF 16S-2230 TD 16/2**  
Capacity: 12,4 liter, Capacity: 21,5 liter (+ intarder)

We are unable to give a standard recommendation for this component. Please contact our service department.

# RENAULT (EU) KERAX KERAX 460 DXI

## EURO 5 (4X2) (2010-2014)


**TRANSMISSION SEMI-AUTOMATIC** Optidriver+ AT 2612TD (Volvo I-Shift) 12/3

Capacity: 14,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 40</b>		

Change every 120000 km/ 24 months

USE		CLIMATE
Normal (preferred)		Moderate
PRODUCT RECOMMENDATION 1		
<b>Syngear MT/LD 75W-80</b>		

Change every 400000 km/ 36 months

**POWER STEERING**

Capacity: 4,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Matic 2032</b>	<b>ATF Almirol</b>	

**COOLING SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 16</b>		

Change every 400000 km/ 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.