

# RENAULT (EU) MIDLUM MIDLUM 180 DXI

## EURO 5 (2009-2014)



**ENGINE** DXi 5 (Deutz TCD)  
Capacity: 12,7 liter

| USE                  | CLIMATE  |
|----------------------|----------|
| Extended drain (max) | Moderate |

| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2      |
|-------------------------------------|-------------------------------|
| <b>Dieselfleet LSP Ultra 10W-30</b> | <b>Dieselfleet MSP 10W-30</b> |

*Change every 80000 km/ 12 months*

| USE            | CLIMATE  |
|----------------|----------|
| Flexible (max) | Moderate |

| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3      |
|-------------------------------------|---------------------------|-------------------------------|
| <b>Armado Synth LSP Ultra 5W-30</b> | <b>Armado Synth 5W-30</b> | <b>Dieselfleet MSP 10W-30</b> |

*Change every 60000 km/ 12 months*

**DIFFERENTIAL REAR** P 08120 (RSS0819A, MS08125)  
Capacity: 7 liter, Capacity: 0,35 liter (each hub)

| USE                | CLIMATE  |
|--------------------|----------|
| Severe (preferred) | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  |
|--------------------------|---------------------------|
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> |

*Change every 240000 km/ 24 months*

| USE                  | CLIMATE  |
|----------------------|----------|
| Normal (alternative) | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |
|-----------------------------|------------------------------------|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |

*Change every 240000 km/ 24 months*

| USE                | CLIMATE  |
|--------------------|----------|
| Normal (preferred) | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  |
|--------------------------|---------------------------|
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> |

*Change every 400000 km/ 36 months*

| USE                  | CLIMATE  |
|----------------------|----------|
| Severe (alternative) | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |
|-----------------------------|------------------------------------|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |

*Change every 120000 km/ 24 months*

# RENAULT (EU) MIDLUM MIDLUM 180 DXI

## EURO 5 (2009-2014)


**TRANSMISSION AUTOMATIC** Allison S2500 5/1

Capacity: 10 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>SP Matic 2032</b>     | <b>ATF Almirol</b>       |          |

Change every 80000 km/ 24 months

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Severe                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>SP Matic 2032</b>     | <b>ATF Almirol</b>       |          |

Change every 20000 km/ 6 months

**TRANSMISSION MANUAL** ZF 6S-800 TO 6/1

Capacity: 10,4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

**HYDRAULIC CLUTCH SYSTEM**

| USE                              |                           | CLIMATE  |
|----------------------------------|---------------------------|----------|
| Normal                           |                           | Moderate |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  |          |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |          |

**POWER STEERING**

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>SP Matic 2032</b>     | <b>ATF Almirol</b>       |          |

**COOLING SYSTEM**

| USE                           |                          | CLIMATE  |
|-------------------------------|--------------------------|----------|
| Normal                        |                          | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.