

RENAULT (EU) MIDLUM MIDLUM 220 DXI

EURO 4/5 (2006-2009)



ENGINE DXi 5 (Deutz TCD)
Capacity: 13,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet MSP 10W-30

PRODUCT RECOMMENDATION 2

Dieselfleet CD+ 15W-40*Change every 50000 km/ 24 months*

USE	CLIMATE
Normal (alternative)	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet CD+ 15W-40*Change every 30000 km/ 24 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet MSP 10W-30

PRODUCT RECOMMENDATION 2

Dieselfleet CD+ 15W-40*Change every 20000 km/ 24 months*

USE	CLIMATE
Severe (alternative)	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet CD+ 15W-40*Change every 20000 km/ 24 months*

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet MSP 10W-30

PRODUCT RECOMMENDATION 2

Dieselfleet CD+ 15W-40*Change every 80000 km/ 24 months*

RENAULT (EU) MIDLUM MIDLUM 220 DXI

EURO 4/5 (2006-2009)



DIFFERENTIAL REAR P 08120 (RSS0819A, MS08125)
Capacity: 7,7 liter, Capacity: 0,35 liter (each hub)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube HS GL-5 80W-140

Change every 120000 km/ 24 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube HS GL-5 80W-140

Change every 80000 km/ 12 months

DIFFERENTIAL REAR P 11140 (RSS1125A)
Capacity: 13,5 liter, Capacity: 0,5 liter (each hub)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube HS GL-5 80W-140	Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140

Change every 120000 km/ 24 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube HS GL-5 80W-140	Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140

Change every 80000 km/ 12 months

DIFFERENTIAL REAR P 11150 (RSS1132A)
Capacity: 16 liter, Capacity: 0,5 liter (each hub)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube HS GL-5 80W-140	Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140

Change every 120000 km/ 24 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube HS GL-5 80W-140	Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140

Change every 80000 km/ 12 months

RENAULT (EU) MIDLUM MIDLUM 220 DXI

EURO 4/5 (2006-2009)



DIFFERENTIAL REAR P 1191 (RSH1140C)
Capacity: 18,3 liter, Capacity: 0,4 liter (each hub)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

Change every 120000 km/ 24 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

Change every 80000 km/ 24 months

TRANSMISSION MANUAL ZF 6S-850 OD 6/1
Capacity: 7,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		

Change every 240000 km/ 24 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		

Change every 200000 km/ 24 months

TRANSMISSION MANUAL ZTO1109 (ZF 9S-1110) 9/1
Capacity: 8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		

Change every 240000 km/ 24 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		

Change every 200000 km/ 24 months

RENAULT (EU) MIDLUM MIDLUM 220 DXI

EURO 4/5 (2006-2009)



HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.