RENAULT (EU) PREMIUM EURO 4/5 PREMIUM 310 DXI EURO 5 (4X2/6X2) (2009-2014)



ENGINE DXi 7 Capacity: 25,3 liter USE CLIMATE Extended drain (max) Moderate PRODUCT RECOMMENDATION 1 **PRODUCT RECOMMENDATION 2 Dieselfleet LSP Ultra 10W-30 Dieselfleet MSP 10W-30** Change every 100000 km/ 12 months USE CLIMATE Flexible (max) Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 **PRODUCT RECOMMENDATION 3** Armado Synth LSP Ultra 5W-30 **Dieselfleet MSP 10W-30** Armado Synth 5W-30

Change every 80000 km/ 12 months

DIFFERENTIAL REAR P MS 13150 Capacity: 17 liter		
USE		CLIMATE
Severe (preferred)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
Change every 240000 km/ 24 months		
USE		CLIMATE
Normal (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 240000 km/ 24 months		
USE		CLIMATE
Normal (preferred)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
Change every 400000 km/ 36 months		
USE		CLIMATE
Severe (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 120000 km/ 24 months		

RENAULT (EU) PREMIUM EURO 4/5 PREMIUM 310 DXI EURO 5 (4X2/6X2) (2009-2014)



TRANSMISSION AUTOMATIC Allison Capacity: 28-31 liter		
USE		CLIMATE
Long distance		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	
Change every 40000 km/ 12 months		
USE		CLIMATE
All other conditions		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Change every 20000 km/ 6 months

TRANSMISSION MANUAL ZTO1109 (ZF 9S-1110) 9/1

Capacity: 8 liter, Capacity: 18 liter (+ intarder)

We are unable to give a standard recommendation for this component. Please contact our service department.

POWER STEERING Capacity: 4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

COOLING SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 16	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.