RENAULT (EU) PREMIUM EURO 4/5 PREMIUM 340 DXI EURO 5 (4X2/6X2) (2009-



2014)

| ENGINE DXi 7 Capacity: 25,3 liter | | |
|--------------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Extended drain (max) | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Dieselfleet LSP Ultra 10W-30 | Dieselfleet MSP 10W-30 | |
| Change every 100000 km/ 12 months | | · |
| USE | | CLIMATE |
| Flexible (max) | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Armado Synth LSP Ultra 5W-30 | Armado Synth 5W-30 | Dieselfleet MSP 10W-30 |
| Change every 80000 km/ 12 months | | |

| DIFFERENTIAL REAR P 13170 (RSS1344C) Capacity: 17 liter | | | |
|---|--------------------------|----------|--|
| USE | | CLIMATE | |
| Severe (preferred) | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| SP Gear 1011 | Syngear TDL 75W-90 | | |

Change every 240000 km/24 months

| USE | | CLIMATE |
|--------------------------|-----------------------------|----------|
| Normal (alternative) | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Change every 240000 km/24 months

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal (preferred) | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| SP Gear 1011 | Syngear TDL 75W-90 | |

Change every 400000 km/36 months

| USE | | CLIMATE |
|---------------------------------|-----------------------------|----------|
| Severe (alternative) | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| Change every 120000 km/24 mont. | hs | |

PRODUCT RECOMMENDATION

RENAULT (EU) PREMIUM EURO 4/5 PREMIUM 340 DXI EURO 5 (4X2/6X2) (2009-



2014)

| | CLIMATE |
|--------------------------|---------------------------------------|
| | Moderate |
| PRODUCT RECOMMENDATION 2 | |
| ATF Almirol | |
| | |
| | CLIMATE |
| | Moderate |
| PRODUCT RECOMMENDATION 2 | |
| ATF Almirol | |
| , | |
| | ATF Almirol PRODUCT RECOMMENDATION 2 |

TRANSMISSION MANUAL ZF 9S-1310 9/1 Capacity: 8 liter, Capacity: 18 liter (+ intarder)

We are unable to give a standard recommendation for this component. Please contact our service department.

| POWER STEERING Capacity: 4 liter | | | |
|----------------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| SP Matic 2032 | ATF Almirol | | |

| COOLING SYSTEM | |
|--------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Coolant SP 16 | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.