

RENAULT (EU) T SERIES EURO 5 T 520 (4X2 / 6X2) EURO 5 (2014 AND AFTER)

**ENGINE DXi 13**

Capacity: 33 liter (Plastic sump), Capacity: 37 liter (Steel sump)

USE	CLIMATE
Long distance, predominantly flat, max 90km/h, =<44t	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet LSP Ultra 10W-30

PRODUCT RECOMMENDATION 2

Dieselfleet MSP 10W-30*Change every 100000 km/ 12 months*

USE	CLIMATE
Long distance, alternative, predominantly flat, max 90km/h, =<44t	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet MSP 10W-30*Change every 80000 km/ 12 months*

USE	CLIMATE
Long distance, hilly, =<44t	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet LSP Ultra 10W-30

PRODUCT RECOMMENDATION 2

Dieselfleet MSP 10W-30*Change every 75000 km/ 12 months*

USE	CLIMATE
Long distance, alternative, hilly, =<44t	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet MSP 10W-30*Change every 60000 km/ 12 months*

USE	CLIMATE
Long distance, predominantly flat, 45-70t	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet LSP Ultra 10W-30

PRODUCT RECOMMENDATION 2

Dieselfleet MSP 10W-30*Change every 60000 km/ 12 months/ 750 hours*

USE	CLIMATE
Long distance, alternative, predominantly flat, 45-70t	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet MSP 10W-30*Change every 40000 km/ 12 months/ 500 hours*

USE	CLIMATE
Long distance, hilly, 45-70t	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet LSP Ultra 10W-30

PRODUCT RECOMMENDATION 2

Dieselfleet MSP 10W-30*Change every 45000 km/ 12 months/ 600 hours*

RENAULT (EU) T SERIES EURO 5 T 520 (4X2 / 6X2) EURO 5 (2014 AND AFTER)



USE		CLIMATE
Long distance, alternative, hilly, 45-70t		Moderate
PRODUCT RECOMMENDATION 1		
Dieselfleet MSP 10W-30		
Change every 30000 km/ 12 months/ 400 hours		
USE		CLIMATE
Long distance, predominantly flat, 71-80t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	
Change every 45000 km/ 12 months/ 600 hours		
USE		CLIMATE
Long distance, alternative, predominantly flat, 71-80t		Moderate
PRODUCT RECOMMENDATION 1		
Dieselfleet MSP 10W-30		
Change every 30000 km/ 12 months/ 400 hours		
USE		CLIMATE
Long distance, hilly, 71-80t, fuel =<120 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	
Change every 20000 km/ 12 months/ 600 hours		
USE		CLIMATE
Long distance, alternative, hilly, 71-80t		Moderate
PRODUCT RECOMMENDATION 1		
Dieselfleet MSP 10W-30		
Change every 15000 km/ 12 months/ 400 hours		
USE		CLIMATE
Long distance, >80t, fuel =<120 L/100km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	
Change every 20000 km/ 12 months/ 600 hours		
USE		CLIMATE
Long distance, alternative, >80t		Moderate
PRODUCT RECOMMENDATION 1		
Dieselfleet MSP 10W-30		
Change every 15000 km/ 12 months/ 400 hours		

RENAULT (EU) T SERIES EURO 5 T 520 (4X2 / 6X2) EURO 5 (2014 AND AFTER)



USE		CLIMATE
Regional, alternative, =<32t		Moderate
PRODUCT RECOMMENDATION 1		
Dieselfleet MSP 10W-30		
Change every 60000 km/ 12 months		
USE		CLIMATE
Regional, 33-44t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	
Change every 60000 km/ 12 months/ 750 hours		
USE		CLIMATE
Regional, alternative, 33-44t		Moderate
PRODUCT RECOMMENDATION 1		
Dieselfleet MSP 10W-30		
Change every 40000 km/ 12 months/ 500 hours		
USE		CLIMATE
Regional, 45-70t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	
Change every 45000 km/ 12 months/ 600 hours		
USE		CLIMATE
Regional, alternative, 45-70t		Moderate
PRODUCT RECOMMENDATION 1		
Dieselfleet MSP 10W-30		
Change every 30000 km/ 12 months/ 400 hours		
USE		CLIMATE
Distribution, city =<32t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	
Change every 45000 km/ 12 months/ 600 hours		
USE		CLIMATE
Distribution, city, alternative, =<32t		Moderate
PRODUCT RECOMMENDATION 1		
Dieselfleet MSP 10W-30		
Change every 30000 km/ 12 months/ 400 hours		

RENAULT (EU) T SERIES EURO 5 T 520 (4X2 / 6X2) EURO 5 (2014 AND AFTER)



USE		CLIMATE
Regional, =<32t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	
Change every 75000 km/ 12 months		

DIFFERENTIAL REAR RSH1370F Capacity: 18 liter, Capacity: 2 liter (each hub)		
USE		CLIMATE
Long distance, hilly, 71-80t, fuel =<120 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
Change every 200000 km/ 36 months		

USE		CLIMATE
Long distance, alternative, hilly, 71-80t		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 85W-140		
Change every 60000 km/ 12 months		

USE		CLIMATE
Long distance, >80t, fuel =<120 L/100km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
Change every 200000 km/ 36 months		

USE		CLIMATE
Long distance, alternative, >80t		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 85W-140		
Change every 60000 km/ 12 months		

USE		CLIMATE
All other conditions		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
Change every 450000 km/ 36 months		

USE		CLIMATE
All other conditions (alternative)		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 85W-140		
Change every 120000 km/ 12 months		

RENAULT (EU) T SERIES EURO 5 T 520 (4X2 / 6X2) EURO 5 (2014 AND AFTER)

**DIFFERENTIAL REAR HYPOID RSS1344C**

Capacity: 12,5 liter

USE	CLIMATE
Long distance, hilly, 71-80t, fuel =<120 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1011	Syngear TDL 75W-90

Change every 200000 km/ 36 months

USE	CLIMATE
Long distance, alternative, hilly, 71-80t	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 85W-140	

Change every 60000 km/ 12 months

USE	CLIMATE
Long distance, >80t, fuel =<120 L/100km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1011	Syngear TDL 75W-90

Change every 200000 km/ 36 months

USE	CLIMATE
Long distance, alternative, >80t	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 85W-140	

Change every 60000 km/ 12 months

USE	CLIMATE
All other conditions	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1011	Syngear TDL 75W-90

Change every 450000 km/ 36 months

USE	CLIMATE
All other conditions (alternative)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 85W-140	

*Change every 120000 km/ 12 months***RETARDER RET-TH**

Capacity: 5,4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

RENAULT (EU) T SERIES EURO 5 T 520 (4X2 / 6X2) EURO 5 (2014 AND AFTER)



TRANSMISSION SEMI-AUTOMATIC Optidriver, AT 2612E (Volvo I-Shift) 12/3
Capacity: 14,5 liter, Capacity: 15,5 liter (+ PTO)

USE	CLIMATE
Long distance, hilly, 71-80t, fuel =<120 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1011	Syngear TDL 75W-90

Change every 200000 km/ 36 months

USE	CLIMATE
Long distance, alternative, hilly, 71-80t	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Syngear MT/LD 75W-80	

Change every 200000 km/ 36 months

USE	CLIMATE
All other conditions	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1011	Syngear TDL 75W-90

Change every 450000 km/ 36 months

USE	CLIMATE
All other conditions (alternative)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Syngear MT/LD 75W-80	

Change every 450000 km/ 36 months

HYDRAULIC CAB TILT SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Matic 2032	ATF Almirol

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Perlus H 15	

RENAULT (EU) T SERIES EURO 5 T 520 (4X2 / 6X2) EURO 5 (2014 AND AFTER)



HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

COOLING SYSTEM

Capacity: 45 liter, Capacity: 58 liter (+ retarder)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.