

SCANIA BUS CHASSIS K/N SERIES K340 IB (4X2, 6X2*4) (2006 AND AFTER)



ENGINE DC12
Capacity: 26,7 liter

USE	CLIMATE
Long distance	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40	Armado Synth 10W-40

Change every 60000 km

USE	CLIMATE
Long distance	Cold

PRODUCT RECOMMENDATION 1		
Armado Synth LSP Ultra 5W-30		

Change every 60000 km

USE	CLIMATE
Regional	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40	Armado Synth 10W-40

Change every 45000 km

USE	CLIMATE
Regional	Cold

PRODUCT RECOMMENDATION 1		
Armado Synth LSP Ultra 5W-30		

Change every 45000 km

USE	CLIMATE
Regional, extended	Moderate

PRODUCT RECOMMENDATION 1		
Armado Synth 10W-40		

Change every 60000 km

USE	CLIMATE
City bus	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40	Armado Synth 10W-40

Change every 30000 km/ 36 months

USE	CLIMATE
City bus	Cold

PRODUCT RECOMMENDATION 1		
Armado Synth LSP Ultra 5W-30		

Change every 30000 km/ 36 months

SCANIA BUS CHASSIS K/N SERIES K340 IB (4X2, 6X2*4) (2006 AND AFTER)



USE		CLIMATE
City bus, extended		Moderate
PRODUCT RECOMMENDATION 1		
Armado Synth 10W-40		
Change every 45000 km		

DIFFERENTIAL REAR HYPOID R 660 Capacity: 12,5 liter		
USE		CLIMATE
Regional		Moderate
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		
Change every 120000 km		

USE		CLIMATE
City bus		Moderate
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		
Change every 90000 km		

TRANSMISSION AUTOMATIC ZF 6HP602C 6/1 Capacity: 30 liter (Dry fill), Capacity: 15 liter (Service fill)		
We are unable to give a standard recommendation for this component. Please contact our service department.		

TRANSMISSION MANUAL GR 801 R 8/1 Capacity: 11 liter		
USE		CLIMATE
Long distance		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		
Change every 240000 km		

USE		CLIMATE
Long distance		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90
Change every 240000 km		

SCANIA BUS CHASSIS K/N SERIES K340 IB (4X2, 6X2*4) (2006 AND AFTER)



USE		CLIMATE
Regional		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 120000 km

USE		CLIMATE
Regional		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90

Change every 120000 km

USE		CLIMATE
City bus		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 90000 km

USE		CLIMATE
City bus		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90

Change every 90000 km

TRANSMISSION MANUAL GR 875 (R) 8/1 Capacity: 15 liter

USE		CLIMATE
Long distance		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 360000 km

USE		CLIMATE
Regional		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 120000 km

USE		CLIMATE
Regional		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90

Change every 120000 km

SCANIA BUS CHASSIS K/N SERIES K340 IB (4X2, 6X2*4) (2006 AND AFTER)



USE		CLIMATE
City bus		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 90000 km

USE		CLIMATE
City bus		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90

Change every 90000 km

HYDRAULIC DAMPER Opticruise Capacity: 0,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

HYDRAULIC STEERING SYSTEM TRAILING AXLE (6x2*4)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
ATF Dexron II-D	ATF-A	

HYDRAULIC SYSTEM VENTILATOR Capacity: 15 liter (Dry fill), Capacity: 8,5 liter (Service fill)		
USE		CLIMATE
Long distance		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Change every 240000 km

USE		CLIMATE
Long distance		Moderate
PRODUCT RECOMMENDATION 1		
Armado Synth 5W-30		

Change every 240000 km

SCANIA BUS CHASSIS K/N SERIES K340 IB (4X2, 6X2*4) (2006 AND AFTER)



USE		CLIMATE
Regional		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Change every 120000 km

USE		CLIMATE
Regional		Moderate
PRODUCT RECOMMENDATION 1		
Armado Synth 5W-30		

Change every 120000 km

USE		CLIMATE
City bus		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Change every 90000 km

USE		CLIMATE
City bus		Moderate
PRODUCT RECOMMENDATION 1		
Armado Synth 5W-30		

Change every 90000 km

POWER STEERING

USE		CLIMATE
Long distance		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
ATF Dexron II-D	ATF-A	

Change every 240000 km

USE		CLIMATE
Regional		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
ATF Dexron II-D	ATF-A	

Change every 120000 km

USE		CLIMATE
City bus		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
ATF Dexron II-D	ATF-A	

Change every 90000 km

SCANIA BUS CHASSIS K/N SERIES K340 IB (4X2, 6X2*4) (2006 AND AFTER)



CENTRAL LUBRICATION SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

USE		CLIMATE
All conditions		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 600000 km/ 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.