PRODUCT RECOMMENDATION

SCANIA G SERIES G-230 EURO 4 (6X4, 8X4) (2008-2009)

ENGINE DC9 16 230 Euro 4
Capacity: 31 liter, Filter capacity: 1 liter

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40	**Armado Synth LSP 10W-40**	**Armado Synth 10W-40**
Change every 20000 km/ 6 months		

USE		CLIMATE
Construction Site		Cold
PRODUCT RECOMMENDATION 1		
Armado Synth LSP Ultra 5W-30		
Change every 20000 km/ 6 months		

USE		CLIMATE
Distribution		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40	**Armado Synth LSP 10W-40**	**Armado Synth 10W-40**
Change every 30000 km/ 6 months		

USE		CLIMATE
Distribution		Cold
PRODUCT RECOMMENDATION 1		
Armado Synth LSP Ultra 5W-30		
Change every 30000 km/ 6 months		

USE		CLIMATE
Distribution, extended		Moderate
PRODUCT RECOMMENDATION 1		
Armado Synth 10W-40		
Change every 45000 km/ 6 months		

USE		CLIMATE
Distribution (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth 10W-40	**Synfleet SHPD 10W-40**	**Dieselfleet MSP 15W-40**
Change every 15000 km/ 6 months		

USE		CLIMATE
Distribution (alternative)		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth 5W-30	**Dieselfleet LSP Ultra 10W-30**	**Dieselfleet MSP 10W-30**
Change every 15000 km/ 6 months		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

SCANIA G SERIES G-230 EURO 4 (6X4, 8X4) (2008-2009)

USE		CLIMATE
Construction Site (alternative)		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Armado Synth 10W-40	**Synfleet SHPD 10W-40**	**Dieselfleet MSP 15W-40**
Change every 10000 km/ 6 months		

USE		CLIMATE
Construction Site (alternative)		Cold
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Armado Synth 5W-30	**Dieselfleet LSP Ultra 10W-30**	**Dieselfleet MSP 10W-30**
Change every 10000 km/ 6 months		

DIFFERENTIAL REAR LEADING RBP 735 (6x4) (8x4) (6x6)
Capacity: 11,7 liter (Axle gear case), Capacity: 2 liter (each hub)

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		
Change every 80000 km		

USE		CLIMATE
Distribution		Moderate
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		
Change every 120000 km		

DIFFERENTIAL REAR LEADING RBP 835 (6x4) (8x4) (6x6)
Capacity: 12 liter (Axle gear case), Capacity: 0-0 liter (each hub)

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		
Change every 80000 km		

USE		CLIMATE
Distribution		Moderate
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		
Change every 120000 km		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

SCANIA G SERIES G-230 EURO 4 (6X4, 8X4) (2008-2009)

DIFFERENTIAL REAR TRAILING RP 735 (6x4) (8x4) (6x6)
Capacity: 8 liter (Axle gear case), Capacity: 2 liter (each hub)

USE	CLIMATE
Construction Site	Moderate

PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 80000 km

USE	CLIMATE
Distribution	Moderate

PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 120000 km

DIFFERENTIAL REAR TRAILING RP 835 (6x4) (8x4) (6x6)
Capacity: 9,3 liter (Axle gear case), Capacity: 2 liter (each hub)

USE	CLIMATE
Construction Site	Moderate

PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 80000 km

USE	CLIMATE
Distribution	Moderate

PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 120000 km

POWER TAKE OFF
Capacity: 0,5-2,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	**Unigear LS GL-3/GL-5 85W-140**	

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	**SP Gear 1011**	**Syngear TDL 75W-90**

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

SCANIA G SERIES G-230 EURO 4 (6X4, 8X4) (2008-2009)

RETARDER Scania
Capacity: 7,9 liter (Initial fill), Capacity: 7,7 liter (Service fill)

USE	CLIMATE
Construction Site	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	**ATF Almirol**	

Change every 80000 km

USE	CLIMATE
Distribution	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	**ATF Almirol**	

Change every 60000 km

TRANSMISSION AUTOMATIC GA 750/751/765/766/767 (Allison MD) 6/1
Capacity: 27 liter (Overhaul capacity), Capacity: 20 liter (Service fill)

USE	CLIMATE
Construction Site	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	**ATF Almirol**	**ATF Dexron II-D**

Change every 20000 km

USE	CLIMATE
Distribution	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	**ATF Almirol**	**ATF Dexron II-D**

Change every 45000 km

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

SCANIA G SERIES G-230 EURO 4 (6X4, 8X4)
(2008-2009)

TRANSMISSION MANUAL GR 875 (R) 8/1
Capacity: 15 liter, Capacity: 17 liter (+ oil cooler (air cooled)), Capacity: 16 liter (+ oil cooler (liquid cooled))

USE		CLIMATE
Construction Site		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 80000 km

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	**Syngear TDL 75W-90**	**Unigear HS GL-3/GL-5 80W-90**

Change every 80000 km

USE		CLIMATE
Distribution		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 120000 km

USE		CLIMATE
Distribution		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	**Syngear TDL 75W-90**	**Unigear HS GL-3/GL-5 80W-90**

Change every 120000 km

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

SCANIA G SERIES G-230 EURO 4 (6X4, 8X4)
(2008-2009)

TRANSMISSION MANUAL GR 905 (R) 8/1
Capacity: 16,5 liter

USE		CLIMATE
Construction Site		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 80000 km

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	**Syngear TDL 75W-90**	**Unigear HS GL-3/GL-5 80W-90**

Change every 80000 km

USE		CLIMATE
Distribution		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 120000 km

USE		CLIMATE
Distribution		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	**Syngear TDL 75W-90**	**Unigear HS GL-3/GL-5 80W-90**

Change every 120000 km

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

SCANIA G SERIES G-230 EURO 4 (6X4, 8X4) (2008-2009)

TRANSMISSION MANUAL GRS 895 (R) 12/2
Capacity: 15 liter, Capacity: 17 liter (+ oil cooler (air cooled)), Capacity: 16 liter (+ oil cooler (liquid cooled))

USE		CLIMATE
Construction Site		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 80000 km

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	**Syngear TDL 75W-90**	**Unigear HS GL-3/GL-5 80W-90**

Change every 80000 km

USE		CLIMATE
Distribution		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 120000 km

USE		CLIMATE
Distribution		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	**Syngear TDL 75W-90**	**Unigear HS GL-3/GL-5 80W-90**

Change every 120000 km

HYDRAULIC CAB TILT SYSTEM
Capacity: 0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 4036	**SP Matic 2032**	**ATF Almirol**

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Perlus H 15		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

SCANIA G SERIES G-230 EURO 4 (6X4, 8X4) (2008-2009)

HYDRAULIC DAMPER Opticruise
Capacity: 0,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	**ATF Almirol**	**ATF Dexron II-D**

HYDRAULIC SYSTEM VENTILATOR
Capacity: 8 liter, Capacity: 15 liter (Initial fill)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Dieselfleet CD+ 15W-40	**Multifleet SHPD 15W-40**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
Armado Synth 5W-30

HYDRAULIC CLUTCH SYSTEM
Capacity: 0,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	**Drauliquid DOT 3**

Change every 12 months

POWER STEERING
Capacity: 4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
ATF Dexron II-D	**ATF-A**

CENTRAL LUBRICATION SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

SCANIA G SERIES G-230 EURO 4 (6X4, 8X4) (2008-2009)

COOLING SYSTEM Capacity: 30 liter		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Coolant SP 15+**	PRODUCT RECOMMENDATION 2 **Coolant SP 12**	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367