

SCANIA R SERIES R-340 EURO 4 (4X4)

(2006-2009)

**ENGINE DC12**

Capacity: 33 liter, Filter capacity: 2 liter

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40	Armado Synth 10W-40

Change every 20000 km

USE		CLIMATE
Construction Site		Cold
PRODUCT RECOMMENDATION 1		
Armado Synth LSP Ultra 5W-30		

Change every 20000 km

USE		CLIMATE
Construction Site (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth 10W-40	Synfleet SHPD 10W-40	Dieselfleet MSP 15W-40

Change every 10000 km/ 12 months

USE		CLIMATE
Construction Site (alternative)		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth 5W-30	Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30

*Change every 10000 km/ 12 months***DIFFERENTIAL FRONT HUB REDUCTIONS RP 731 (4x4) (6x6)**

Capacity: 13,5 liter (Axle gear case), Capacity: 0,8 liter (each hub)

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

*Change every 80000 km***DIFFERENTIAL REAR HUB REDUCTIONS RP 835**

Capacity: 12 liter (Axle gear case), Capacity: 2 liter (each hub)

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 80000 km

SCANIA R SERIES R-340 EURO 4 (4X4)

(2006-2009)

**POWER TAKE OFF**

Capacity: 0,5-2,5 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90

RETARDER Scania

Capacity: 7,9 liter (Initial fill), Capacity: 7,7 liter (Service fill)

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

*Change every 120000 km***TRANSFERBOX** GTD 800 (4x4)

Capacity: 6,5 liter

USE		CLIMATE
Construction Site		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Change every 20000 km

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90

Change every 20000 km

SCANIA R SERIES R-340 EURO 4 (4X4)

(2006-2009)



TRANSMISSION AUTOMATIC GA 851/852/866/867 (Allison HD) 6/1
Capacity: 50 liter (Overhaul capacity), Capacity: 34 liter (Service fill)

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Change every 20000 km

TRANSMISSION MANUAL GR 875 (R) 8/1
Capacity: 15 liter, Capacity: 17 liter (+ oil cooler (air cooled)), Capacity: 16 liter (+ oil cooler (liquid cooled))

USE		CLIMATE
Construction Site		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 80000 km

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90

Change every 80000 km

TRANSMISSION MANUAL GR 905 (R) 8/1
Capacity: 16,5 liter

USE		CLIMATE
Construction Site		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 80000 km

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90

Change every 80000 km

SCANIA R SERIES R-340 EURO 4 (4X4)

(2006-2009)

**TRANSMISSION MANUAL GRS 895 (R) 12/2**

Capacity: 15 liter, Capacity: 17 liter (+ oil cooler (air cooled)), Capacity: 16 liter (+ oil cooler (liquid cooled))

USE		CLIMATE
Construction Site		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 80000 km

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90

*Change every 80000 km***TRANSMISSION MANUAL GRS 905 12/2**

Capacity: 16,5 liter

USE		CLIMATE
Construction Site		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 80000 km

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90

*Change every 80000 km***TRANSMISSION MANUAL GRSO 905 12/2**

USE		CLIMATE
Construction Site		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 80000 km

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90

Change every 80000 km

SCANIA R SERIES R-340 EURO 4 (4X4)

(2006-2009)



HYDRAULIC CAB TILT SYSTEM

Capacity: 0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 4036	SP Matic 2032	ATF Almirol

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Perlus H 15		

HYDRAULIC DAMPER Opticruise

Capacity: 0,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

HYDRAULIC SYSTEM VENTILATOR

Capacity: 8 liter, Capacity: 15 liter (Initial fill)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Armado Synth 5W-30		

HYDRAULIC CLUTCH SYSTEM

Capacity: 0,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Change every 12 months

SCANIA R SERIES R-340 EURO 4 (4X4)

(2006-2009)



POWER STEERING

Capacity: 4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
ATF Dexron II-D	ATF-A	

CENTRAL LUBRICATION SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 50 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.