

SCANIA R SERIES R-440 EURO 5 (6X4, 8X4)

(2008 AND AFTER)

**ENGINE** DC13 10 Euro 5

Capacity: 40 liter, Filter capacity: 1 liter

USE	CLIMATE
Long distance, alternative, =<45t	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40	Armado Synth 10W-40

Change every 45000 km

USE	CLIMATE
Long distance, alternative, =<45t	Cold

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Armado Synth LSP Ultra 5W-30	Armado Synth 5W-30	

Change every 45000 km

USE	CLIMATE
Construction Site	Moderate

PRODUCT RECOMMENDATION 1		
Armado Synth 10W-40		

Change every 20000 km

USE	CLIMATE
Construction Site	Cold

PRODUCT RECOMMENDATION 1		
Armado Synth 5W-30		

Change every 20000 km

USE	CLIMATE
Long distance, extended, =<45t	Moderate

PRODUCT RECOMMENDATION 1		
Armado Synth 10W-40		

Change every 90000 km

USE	CLIMATE
Long distance, =<45t	Moderate

PRODUCT RECOMMENDATION 1		
Armado Synth 10W-40		

Change every 60000 km

USE	CLIMATE
Long distance, =<45t	Cold

PRODUCT RECOMMENDATION 1		
Armado Synth 5W-30		

Change every 60000 km

SCANIA R SERIES R-440 EURO 5 (6X4, 8X4) (2008 AND AFTER)



USE		CLIMATE
Long distance, extended, 45-60t		Moderate
PRODUCT RECOMMENDATION 1		
Armado Synth 10W-40		
<i>Change every 60000 km</i>		
USE		CLIMATE
Long distance, 45-60t		Moderate
PRODUCT RECOMMENDATION 1		
Armado Synth 10W-40		
<i>Change every 45000 km</i>		
USE		CLIMATE
Long distance, 45-60t		Cold
PRODUCT RECOMMENDATION 1		
Armado Synth 5W-30		
<i>Change every 45000 km</i>		
USE		CLIMATE
Long distance, severe, =<60t		Moderate
PRODUCT RECOMMENDATION 1		
Armado Synth 10W-40		
<i>Change every 30000 km/ 36 months</i>		
USE		CLIMATE
Long distance, severe, =<60t		Cold
PRODUCT RECOMMENDATION 1		
Armado Synth 5W-30		
<i>Change every 30000 km/ 36 months</i>		
USE		CLIMATE
Long distance, alternative, 45-60t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40	Armado Synth 10W-40
<i>Change every 30000 km/ 36 months</i>		
USE		CLIMATE
Long distance, alternative, 45-60t		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Armado Synth LSP Ultra 5W-30	Armado Synth 5W-30	
<i>Change every 30000 km/ 36 months</i>		

SCANIA R SERIES R-440 EURO 5 (6X4, 8X4) (2008 AND AFTER)

**DIFFERENTIAL REAR LEADING RB 662 (6x4) (8x4)**

Capacity: 14 liter

USE	CLIMATE
Construction Site	Moderate

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140*Change every 80000 km*

USE	CLIMATE
Distribution	Moderate

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140*Change every 120000 km*

USE	CLIMATE
Long distance, =<45t	Moderate

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140*Change every 240000 km*

USE	CLIMATE
Long distance, severe, =<60t	Moderate

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140*Change every 120000 km*

SCANIA R SERIES R-440 EURO 5 (6X4, 8X4) (2008 AND AFTER)



DIFFERENTIAL REAR LEADING RBP 735 (6x4) (8x4) (6x6)
Capacity: 11,7 liter (Axle gear case), Capacity: 2 liter (each hub)

USE	CLIMATE
Construction Site	Moderate

PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 80000 km

USE	CLIMATE
Distribution	Moderate

PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 120000 km

USE	CLIMATE
Long distance, =<45t	Moderate

PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 240000 km

USE	CLIMATE
Long distance, severe, =<60t	Moderate

PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 120000 km

SCANIA R SERIES R-440 EURO 5 (6X4, 8X4) (2008 AND AFTER)



DIFFERENTIAL REAR LEADING RBP 835 (6x4) (8x4) (6x6)
Capacity: 12 liter (Axle gear case), Capacity: 2 liter (each hub)

USE	CLIMATE
Construction Site	Moderate

PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 80000 km

USE	CLIMATE
Distribution	Moderate

PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 120000 km

USE	CLIMATE
Long distance, =<45t	Moderate

PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 240000 km

USE	CLIMATE
Long distance, severe, =<60t	Moderate

PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 120000 km

SCANIA R SERIES R-440 EURO 5 (6X4, 8X4) (2008 AND AFTER)


DIFFERENTIAL REAR TRAILING R 660 (6x4) (8x4)

Capacity: 12,5 liter

USE	CLIMATE
Construction Site	Moderate

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140*Change every 80000 km*

USE	CLIMATE
Distribution	Moderate

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140*Change every 120000 km*

USE	CLIMATE
Long distance, =<45t	Moderate

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140*Change every 240000 km*

USE	CLIMATE
Long distance, severe, =<60t	Moderate

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140*Change every 120000 km*

SCANIA R SERIES R-440 EURO 5 (6X4, 8X4) (2008 AND AFTER)



DIFFERENTIAL REAR TRAILING RP 735 (6x4) (8x4) (6x6)
Capacity: 8 liter (Axle gear case), Capacity: 2 liter (each hub)

USE	CLIMATE
Construction Site	Moderate

PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 80000 km

USE	CLIMATE
Distribution	Moderate

PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 120000 km

USE	CLIMATE
Long distance, =<45t	Moderate

PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 240000 km

USE	CLIMATE
Long distance, severe, =<60t	Moderate

PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 120000 km

SCANIA R SERIES R-440 EURO 5 (6X4, 8X4) (2008 AND AFTER)



DIFFERENTIAL REAR TRAILING RP 835 (6x4) (8x4) (6x6)
Capacity: 9,3 liter (Axle gear case), Capacity: 2 liter (each hub)

USE	CLIMATE
Construction Site	Moderate

PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 80000 km

USE	CLIMATE
Distribution	Moderate

PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 120000 km

USE	CLIMATE
Long distance, =<45t	Moderate

PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 240000 km

USE	CLIMATE
Long distance, severe, =<60t	Moderate

PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 120000 km

POWER TAKE OFF

Capacity: 0,5-2,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90

SCANIA R SERIES R-440 EURO 5 (6X4, 8X4) (2008 AND AFTER)



RETARDER Scania
Capacity: 7,5-7,9 liter (Initial fill), Capacity: 5-7,7 liter (Service fill)

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Change every 120000 km

USE		CLIMATE
Distribution		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Change every 80000 km

USE		CLIMATE
Long distance, extended, =<45t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Change every 360000 km

USE		CLIMATE
Long distance, severe, =<60t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Change every 120000 km

TRANSMISSION AUTOMATIC GA 851/852/866/867 (Allison HD) 6/1
Capacity: 50 liter (Overhaul capacity), Capacity: 34 liter (Service fill)

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Change every 20000 km

USE		CLIMATE
Distribution		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Change every 45000 km

TRANSMISSION MANUAL GR 905 (R) 8/1
Capacity: 16,5 liter

SCANIA R SERIES R-440 EURO 5 (6X4, 8X4) (2008 AND AFTER)



USE		CLIMATE
Construction Site		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		
<i>Change every 80000 km</i>		
USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90
<i>Change every 80000 km</i>		
USE		CLIMATE
Distribution		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		
<i>Change every 120000 km</i>		
USE		CLIMATE
Distribution		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90
<i>Change every 120000 km</i>		
USE		CLIMATE
Long distance, extended, =<45t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 360000 km</i>		
USE		CLIMATE
Long distance, =<45t		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		
<i>Change every 240000 km</i>		
USE		CLIMATE
Long distance, =<45t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90
<i>Change every 240000 km</i>		

SCANIA R SERIES R-440 EURO 5 (6X4, 8X4) (2008 AND AFTER)



USE		CLIMATE
Long distance, severe, =<60t		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 120000 km

USE		CLIMATE
Long distance, severe, =<60t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90

Change every 120000 km

TRANSMISSION MANUAL GRS 895 (R) 12/2

Capacity: 15 liter, Capacity: 17 liter (+ oil cooler (air cooled)), Capacity: 16 liter (+ oil cooler (liquid cooled))

USE		CLIMATE
Construction Site		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 80000 km

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90

Change every 80000 km

USE		CLIMATE
Distribution		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 120000 km

USE		CLIMATE
Distribution		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90

Change every 120000 km

USE		CLIMATE
Long distance, extended, =<45t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 360000 km

SCANIA R SERIES R-440 EURO 5 (6X4, 8X4)

(2008 AND AFTER)



USE		CLIMATE
Long distance, =<45t		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 240000 km

USE		CLIMATE
Long distance, =<45t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90

Change every 240000 km

USE		CLIMATE
Long distance, severe, =<60t		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 120000 km

USE		CLIMATE
Long distance, severe, =<60t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90

Change every 120000 km

TRANSMISSION MANUAL GRS 905 12/2

Capacity: 16,5 liter

USE		CLIMATE
Construction Site		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 80000 km

USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90

Change every 80000 km

USE		CLIMATE
Distribution		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 120000 km

SCANIA R SERIES R-440 EURO 5 (6X4, 8X4) (2008 AND AFTER)



USE		CLIMATE
Distribution		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90

Change every 120000 km

USE		CLIMATE
Long distance, extended, =<45t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 360000 km

USE		CLIMATE
Long distance, =<45t		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 240000 km

USE		CLIMATE
Long distance, =<45t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90

Change every 240000 km

USE		CLIMATE
Long distance, severe, =<60t		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 120000 km

USE		CLIMATE
Long distance, severe, =<60t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90

Change every 120000 km

TRANSMISSION MANUAL GRSO 905 12/2		
USE		CLIMATE
Construction Site		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 80000 km

SCANIA R SERIES R-440 EURO 5 (6X4, 8X4)

(2008 AND AFTER)



USE		CLIMATE
Construction Site		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90
<i>Change every 80000 km</i>		
USE		CLIMATE
Distribution		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		
<i>Change every 120000 km</i>		
USE		CLIMATE
Distribution		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90
<i>Change every 120000 km</i>		
USE		CLIMATE
Long distance, extended, =<45t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 360000 km</i>		
USE		CLIMATE
Long distance, =<45t		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		
<i>Change every 240000 km</i>		
USE		CLIMATE
Long distance, =<45t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90
<i>Change every 240000 km</i>		
USE		CLIMATE
Long distance, severe, =<60t		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		
<i>Change every 120000 km</i>		

SCANIA R SERIES R-440 EURO 5 (6X4, 8X4) (2008 AND AFTER)



USE		CLIMATE
Long distance, severe, =<60t		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Unigear HS GL-3/GL-5 80W-90
<i>Change every 120000 km</i>		

HYDRAULIC CAB TILT SYSTEM Capacity: 0,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 4036	SP Matic 2032	ATF Almirol
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Perlus H 15		

HYDRAULIC DAMPER Opticruise Capacity: 0,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

HYDRAULIC SYSTEM VENTILATOR Capacity: 8 liter, Capacity: 15 liter (Initial fill)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Armado Synth 5W-30		

SCANIA R SERIES R-440 EURO 5 (6X4, 8X4)

(2008 AND AFTER)



HYDRAULIC CLUTCH SYSTEM

Capacity: 0,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Change every 12 months

POWER STEERING

Capacity: 4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
ATF Dexron II-D	ATF-A	

CENTRAL LUBRICATION SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 44 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.