

# SCANIA COACHES OMNILINK CK310 UA

## 6X2/2 EURO 4 (2006 AND AFTER)



**ENGINE** DC9 18 310 Euro 4  
Capacity: 32-34 liter

USE	CLIMATE
Regional	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Armado Synth LSP Ultra 10W-40</b>	<b>Armado Synth LSP 10W-40</b>	<b>Armado Synth 10W-40</b>

*Change every 45000 km*

USE	CLIMATE
Regional	Cold

PRODUCT RECOMMENDATION 1		
<b>Armado Synth LSP Ultra 5W-30</b>		

*Change every 45000 km*

USE	CLIMATE
Regional, extended	Moderate

PRODUCT RECOMMENDATION 1		
<b>Armado Synth 10W-40</b>		

*Change every 60000 km*

USE	CLIMATE
City bus	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Armado Synth LSP Ultra 10W-40</b>	<b>Armado Synth LSP 10W-40</b>	<b>Armado Synth 10W-40</b>

*Change every 30000 km/ 36 months*

USE	CLIMATE
City bus	Cold

PRODUCT RECOMMENDATION 1		
<b>Armado Synth LSP Ultra 5W-30</b>		

*Change every 30000 km/ 36 months*

USE	CLIMATE
City bus, extended	Moderate

PRODUCT RECOMMENDATION 1		
<b>Armado Synth 10W-40</b>		

*Change every 45000 km*

# SCANIA COACHES OMNILINK CK310 UA

## 6X2/2 EURO 4 (2006 AND AFTER)



### DIFFERENTIAL REAR ADA 1300

USE		CLIMATE
Normal (preferred)		Moderate
PRODUCT RECOMMENDATION 1		
<b>Unigear HS GL-3/GL-5 80W-90</b>		
<i>Change every 150000 km/ 36 months</i>		

### TRANSMISSION AUTOMATIC ZF 5HP594C 5/1

Capacity: 30 liter (Dry fill), Capacity: 15 liter (Service fill)

We are unable to give a standard recommendation for this component. Please contact our service department.

### HYDRAULIC CONTROL SYSTEM ARTICULATED BUS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>ATF Dexron II-D</b>		

### HYDRAULIC SYSTEM VENTILATOR

Capacity: 15 liter (Dry fill), Capacity: 8,5 liter (Service fill)

USE		CLIMATE
Regional		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>	

*Change every 120000 km*

USE		CLIMATE
Regional		Moderate
PRODUCT RECOMMENDATION 1		
<b>Armado Synth 5W-30</b>		

*Change every 120000 km*

USE		CLIMATE
City bus		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>	

*Change every 90000 km*

USE		CLIMATE
City bus		Moderate
PRODUCT RECOMMENDATION 1		
<b>Armado Synth 5W-30</b>		

*Change every 90000 km*

# SCANIA COACHES OMNILINK CK310 UA

## 6X2/2 EURO 4 (2006 AND AFTER)



### POWER STEERING

USE	CLIMATE
Regional	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>ATF Dexron II-D</b>	<b>ATF-A</b>	

*Change every 120000 km*

USE	CLIMATE
City bus	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>ATF Dexron II-D</b>	<b>ATF-A</b>	

*Change every 90000 km*

### CENTRAL LUBRICATION SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

### COOLING SYSTEM

USE	CLIMATE
All conditions	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	

*Change every 600000 km/ 36 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*