

SEDDON ATKINSON EUROMOVER

EUROMOVER L626275FRS (6X2) (2001-2007)



ENGINE Iveco F2BE0681C Cursor 8
Capacity: 23 liter, Filter capacity: 2,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth 5W-30	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 80000 km/ 1600 hours/ 12 months

DIFFERENTIAL REAR Meritor U 177 E
Capacity: 18,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube HS GL-5 80W-140	Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140

Check every 80000 km/ 12 months/ 1600 hours, change every 160000 km/ 3200 hours

TRANSMISSION AUTOMATIC Allison MD 3560P 5/1
Capacity: 18 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Check every 80000 km/ 12 months/ 1600 hours, change every 120000 km/ 3000 hours/ 36 months

HYDRAULIC CAB TILT SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 15		

Check every 80000 km/ 12 months/ 1600 hours

POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Check every 80000 km/ 12 months/ 1600 hours

SEDDON ATKINSON EUROMOVER

EUROMOVER L626275FRS (6X2) (2001-2007)



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 80000 km/ 12 months/ 1600 hours

WHEEL BEARINGS OIL LUBRICATED Meritor U 177 E

Capacity: 0,35 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube HS GL-5 80W-140	Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140

Check every 80000 km/ 12 months/ 1600 hours, change every 160000 km/ 3200 hours

COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 80000 km/ 12 months/ 1600 hours, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.