

SEDDON ATKINSON STRATO STRATO

17.340C (4X2) (1994-2001)



ENGINE Cummins NTE340
Capacity: 42 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1
Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 2
Multifleet SHPD 15W-40

Change every 32000 km/ 3 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 2
Armado Synth 5W-30

PRODUCT RECOMMENDATION 3
Dieselfleet LSP Ultra 10W-30

Change every 32000 km/ 3 months

DIFFERENTIAL REAR Rockwell S180E
Capacity: 20,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
Gearlube HS GL-5 80W-140

PRODUCT RECOMMENDATION 2
Gearlube GL-5 85W-140

PRODUCT RECOMMENDATION 3
Unigear LS GL-3/GL-5 85W-140

Check every 16000 km/ 2 months, change every 80000 km/ 12 months

TRANSMISSION MANUAL Eaton TS 12612 12/3
Capacity: 12,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
Gearlube GL-4 80W-90

PRODUCT RECOMMENDATION 2
Unigear HS GL-3/GL-5 80W-90

Check every 16000 km/ 2 months, change every 80000 km/ 12 months

HYDRAULIC CAB TILT SYSTEM
Capacity: 0,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
Perlus H 15

Check every 16000 km/ 2 months

SEDDON ATKINSON STRATO STRATO

17.340C (4X2) (1994-2001)



HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 16000 km/ 2 months, change every 80000 km/ 12 months

POWER STEERING

Capacity: 3,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Change every 80000 km/ 12 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 40,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Change every 80000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.