

SEDDON ATKINSON STRATO STRATO

26.275L (6X4) (1994-2001)



ENGINE Cummins LTAA10-275
Capacity: 34 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Change every 32000 km/ 3 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Synfleet SHPD 10W-40	Armado Synth 5W-30	Dieselfleet LSP Ultra 10W-30

Change every 32000 km/ 3 months

DIFFERENTIAL REAR LEADING Rockwell RT153
Capacity: 20,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube HS GL-5 80W-140	Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140

Check every 16000 km/ 2 months, change every 80000 km/ 12 months

DIFFERENTIAL REAR TRAILING Rockwell RT153
Capacity: 16,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube HS GL-5 80W-140	Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140

Check every 16000 km/ 2 months, change every 80000 km/ 12 months

TRANSMISSION MANUAL Eaton RT 11609 A 9/1
Capacity: 12 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 16000 km/ 2 months, change every 80000 km/ 12 months

SEDDON ATKINSON STRATO STRATO

26.275L (6X4) (1994-2001)


TRANSMISSION MANUAL Eaton TS 12612 12/3

Capacity: 12,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 16000 km/ 2 months, change every 80000 km/ 12 months

TRANSMISSION MANUAL ZF 9S-109 9/1

Capacity: 8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	

Check every 16000 km/ 2 months, change every 80000 km/ 12 months

HYDRAULIC CAB TILT SYSTEM

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 15		

Check every 16000 km/ 2 months

HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 16000 km/ 2 months, change every 80000 km/ 12 months

POWER STEERING

Capacity: 4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Change every 80000 km/ 12 months

SEDDON ATKINSON STRATO STRATO

26.275L (6X4) (1994-2001)



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 29,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Change every 80000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.