

VOLVO (EU) FM-13 EURO 4/5 FM 13-360 4X4 EURO 4/5 INC. D13A (2006 AND AFTER)



ENGINE D13A
Capacity: 42 liter

USE	CLIMATE
Regional, extended, 33-44t, fuel =<50 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40

Change every 60000 km/ 12 months/ 750 hours

USE	CLIMATE
Regional, 33-44t, fuel =<50 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40	Synfleet SHPD 10W-40

Change every 40000 km/ 12 months/ 500 hours

USE	CLIMATE
Distribution, city, =<32t, fuel =<39 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40	Synfleet SHPD 10W-40

Change every 60000 km/ 12 months

USE	CLIMATE
Distribution, extended, city, =<32t, fuel =<64 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40

Change every 45000 km/ 12 months/ 600 hours

USE	CLIMATE
Construction Site, very hilly, >80t	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40	Synfleet SHPD 10W-40

Change every 400 hours/ 12 months

USE	CLIMATE
Construction Site, extended, very hilly, >80t	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40

Change every 600 hours/ 12 months

USE	CLIMATE
Construction Site, hilly, 45-80t, fuel =<64 L/100 km	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40	Synfleet SHPD 10W-40

Change every 15000 km/ 12 months/ 400 hours

VOLVO (EU) FM-13 EURO 4/5 FM 13-360 4X4 EURO 4/5 INC. D13A (2006 AND AFTER)



USE		CLIMATE
Construction Site, extended, hilly, 45-80t, fuel <64 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40
<i>Change every 20000 km/ 12 months/ 600 hours</i>		
USE		CLIMATE
Long distance, predominantly flat/hilly >80t, fuel >64 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40	Synfleet SHPD 10W-40
<i>Change every 15000 km/ 12 months/ 400 hours</i>		
USE		CLIMATE
Long distance, extended, predominantly flat/hilly >80t, fuel >64 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40
<i>Change every 20000 km/ 12 months/ 600 hours</i>		
USE		CLIMATE
Long distance, hilly, 71-80t, fuel =<64 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40	Synfleet SHPD 10W-40
<i>Change every 30000 km/ 12 months/ 400 hours</i>		
USE		CLIMATE
Regional, 45-70t, fuel =<64 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40	Synfleet SHPD 10W-40
<i>Change every 30000 km/ 12 months/ 400 hours</i>		
USE		CLIMATE
Regional, extended, 45-70t, fuel =<64 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40	Synfleet SHPD 10W-40
<i>Change every 45000 km/ 12 months/ 600 hours</i>		
USE		CLIMATE
Long distance, predominantly flat, 71-80t, fuel =<64 L/100 km		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40	Synfleet SHPD 10W-40
<i>Change every 30000 km/ 12 months/ 400 hours</i>		

VOLVO (EU) FM-13 EURO 4/5 FM 13-360 4X4 EURO 4/5 INC. D13A (2006 AND AFTER)



USE Long distance, extended, hilly, 45-70t, fuel =<64 L/100 km		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Armado Synth LSP Ultra 5W-30	PRODUCT RECOMMENDATION 2 Armado Synth LSP Ultra 10W-40	PRODUCT RECOMMENDATION 3 Armado Synth LSP 10W-40
Change every 45000 km/ 12 months/ 600 hours		
USE Long distance, hilly, 45-70t, fuel =<64 L/100 km		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Armado Synth LSP Ultra 10W-40	PRODUCT RECOMMENDATION 2 Armado Synth LSP 10W-40	PRODUCT RECOMMENDATION 3 Synfleet SHPD 10W-40
Change every 30000 km/ 12 months/ 400 hours		
USE Construction site, extended, hilly, =<32t, fuel =<50 L/100 km		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Armado Synth LSP Ultra 5W-30	PRODUCT RECOMMENDATION 2 Armado Synth LSP Ultra 10W-40	PRODUCT RECOMMENDATION 3 Armado Synth LSP 10W-40
Change every 60000 km/ 12 months/ 750 hours		
USE Construction site, hilly, =<32t, fuel =<50 L/100 km		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Armado Synth LSP Ultra 10W-40	PRODUCT RECOMMENDATION 2 Armado Synth LSP 10W-40	PRODUCT RECOMMENDATION 3 Synfleet SHPD 10W-40
Change every 40000 km/ 12 months/ 500 hours		
USE Long distance, predominantly flat, 45-70t, fuel =<50 L/100 km		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Armado Synth LSP Ultra 10W-40	PRODUCT RECOMMENDATION 2 Armado Synth LSP 10W-40	PRODUCT RECOMMENDATION 3 Synfleet SHPD 10W-40
Change every 40000 km/ 12 months/ 500 hours		
USE Long distance, extended, predominantly flat, 45-70t, fuel =<50 L/100 km		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Armado Synth LSP Ultra 5W-30	PRODUCT RECOMMENDATION 2 Armado Synth LSP Ultra 10W-40	PRODUCT RECOMMENDATION 3 Armado Synth LSP 10W-40
Change every 60000 km/ 12 months/ 750 hours		
USE Long distance, hilly, PTO use + idle time < 25% of total operating time, =<44t, fuel =<39 L/100 km		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Armado Synth LSP Ultra 10W-40	PRODUCT RECOMMENDATION 2 Armado Synth LSP 10W-40	PRODUCT RECOMMENDATION 3 Synfleet SHPD 10W-40
Change every 60000 km/ 12 months		

VOLVO (EU) FM-13 EURO 4/5 FM 13-360 4X4 EURO 4/5 INC. D13A (2006 AND AFTER)



USE Long distance, extended, hilly, PTO use + idle time < 25% of total operating time, =<44t, fuel =<39 L/100 km		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Armado Synth LSP Ultra 5W-30	PRODUCT RECOMMENDATION 2 Armado Synth LSP Ultra 10W-40	PRODUCT RECOMMENDATION 3 Armado Synth LSP 10W-40
Change every 75000 km/ 12 months		
USE Long distance, predominantly flat, max 90km/h, =<44t, fuel =< 33 L/100 km		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Armado Synth LSP Ultra 10W-40	PRODUCT RECOMMENDATION 2 Armado Synth LSP 10W-40	PRODUCT RECOMMENDATION 3 Synfleet SHPD 10W-40
Change every 60000 km/ 12 months		
USE Long distance, extended, predominantly flat, max 90km/h, =<44t, fuel =< 33 L/100 km		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Armado Synth LSP Ultra 5W-30	PRODUCT RECOMMENDATION 2 Armado Synth LSP Ultra 10W-40	PRODUCT RECOMMENDATION 3 Armado Synth LSP 10W-40
Change every 100000 km/ 12 months		
USE Distribution, city, =<32t, fuel =<64 L/100 km		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Armado Synth LSP Ultra 10W-40	PRODUCT RECOMMENDATION 2 Armado Synth LSP 10W-40	PRODUCT RECOMMENDATION 3 Synfleet SHPD 10W-40
Change every 30000 km/ 12 months/ 400 hours		
USE Construction site, extended, hilly, 33-44t, fuel =<64 L/100 km		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Armado Synth LSP Ultra 5W-30	PRODUCT RECOMMENDATION 2 Armado Synth LSP Ultra 10W-40	PRODUCT RECOMMENDATION 3 Armado Synth LSP 10W-40
Change every 45000 km/ 12 months/ 600 hours		
USE Construction site, hilly, 33-44t, =<64 L/100 km		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Armado Synth LSP Ultra 10W-40	PRODUCT RECOMMENDATION 2 Armado Synth LSP 10W-40	PRODUCT RECOMMENDATION 3 Synfleet SHPD 10W-40
Change every 30000 km/ 12 months/ 400 hours		
USE Long distance, extended, hilly, 71-80t, fuel =<64 L/100 km		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Armado Synth LSP Ultra 5W-30	PRODUCT RECOMMENDATION 2 Armado Synth LSP Ultra 10W-40	PRODUCT RECOMMENDATION 3 Armado Synth LSP 10W-40
Change every 45000 km/ 12 months/ 600 hours		

VOLVO (EU) FM-13 EURO 4/5 FM 13-360 4X4 EURO 4/5 INC. D13A (2006 AND AFTER)

**DIFFERENTIAL FRONT FAA11**

Capacity: 11,5 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Change every 120000 km/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

*Change every 120000 km/ 12 months***DIFFERENTIAL FRONT FS0910HZ (FA-DRIVE)**

Capacity: 11,5 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Change every 120000 km/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

*Change every 120000 km/ 12 months***DIFFERENTIAL REAR HYPOID RS1356SV**

Capacity: 8,5-9 liter

USE		CLIMATE
Extended, all other conditions		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 400000 km/ 36 months

USE		CLIMATE
Extended, very severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 200000 km/ 36 months

VOLVO (EU) FM-13 EURO 4/5 FM 13-360 4X4 EURO 4/5 INC. D13A (2006 AND AFTER)



USE		CLIMATE
Extended, very severe+		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 2500 hours</i>		
USE		CLIMATE
All other conditions		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
<i>Change every 120000 km/ 12 months</i>		
USE		CLIMATE
All other conditions		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube HS GL-5 80W-140		
<i>Change every 120000 km/ 12 months</i>		
USE		CLIMATE
Very severe		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
<i>Change every 60000 km/ 12 months</i>		
USE		CLIMATE
Very severe		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube HS GL-5 80W-140		
<i>Change every 60000 km/ 12 months</i>		
USE		CLIMATE
Very severe+		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
<i>Change every 600 hours</i>		
USE		CLIMATE
Very severe+		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube HS GL-5 80W-140		
<i>Change every 600 hours</i>		



VOLVO (EU) FM-13 EURO 4/5 FM 13-360 4X4 EURO 4/5 INC. D13A (2006 AND AFTER)

**POWER TAKE OFF**

Capacity: 4,5-5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 180000 km/ 12 months

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 40	SP Gear 1011	Syngear TDL 75W-90

Change every 120000 km/ 12 months

USE		CLIMATE
Alternative (acceptable)		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 30	Syngear MT/LD 75W-80	Gearlube GL-4 80W

Change every 120000 km/ 12 months

VOLVO (EU) FM-13 EURO 4/5 FM 13-360 4X4 EURO 4/5 INC. D13A (2006 AND AFTER)

**RETARDER RET-TH**

Capacity: 6,1 liter (Dry fill), Capacity: 5,4 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Armado Synth LSP Ultra 10W-40

Change every 135000 km/ 24 months

USE	CLIMATE
Normal (alternative)	Moderate

PRODUCT RECOMMENDATION 1

Armado Synth 10W-40

Change every 120000 km/ 24 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Armado Synth LSP Ultra 10W-40

Change every 90000 km/ 24 months

USE	CLIMATE
Very severe	Moderate

PRODUCT RECOMMENDATION 1

Armado Synth LSP Ultra 10W-40

Change every 65000 km/ 24 months

TRANSFERBOX Volvo VT2501TB

Capacity: 5,5 liter

USE	CLIMATE
Extended	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear MT/LD 75W-80

PRODUCT RECOMMENDATION 3

Syngear TDL 75W-90

Change every 180000 km/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 40

PRODUCT RECOMMENDATION 2

SP Gear 1011

PRODUCT RECOMMENDATION 3

Syngear TDL 75W-90

Change every 120000 km/ 12 months

TRANSMISSION AUTOMATED I-Shift AT2412C 12/4

Capacity: 16 liter, Capacity: 16,8 liter (+ oil cooler)

VOLVO (EU) FM-13 EURO 4/5 FM 13-360 4X4 EURO 4/5 INC. D13A (2006 AND AFTER)



USE		CLIMATE
Normal service category 1, 2, 3, 4		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 400000 km/ 36 months</i>		
USE		CLIMATE
Normal service category 1, 2		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		
<i>Change every 400000 km/ 36 months</i>		
USE		CLIMATE
Normal (alternative) service categories 1, 2		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 40	SP Gear 1011	Syngear TDL 75W-90
<i>Change every 120000 km/ 12 months</i>		
USE		CLIMATE
Severe service category 1, 2		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		
<i>Change every 200000 km/ 36 months</i>		
USE		CLIMATE
Severe service category 1, 2, 3, 4		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 200000 km/ 36 months</i>		
USE		CLIMATE
Severe (alternative) service categories 1, 2		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 40	SP Gear 1011	Syngear TDL 75W-90
<i>Change every 60000 km/ 12 months</i>		
USE		CLIMATE
Extremely severe, service categories 1, 2, 3, 4		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 2500 hours</i>		

TRANSMISSION AUTOMATED I-Shift AT2512C 12/2
Capacity: 16 liter, Capacity: 16,8 liter (+ oil cooler)

VOLVO (EU) FM-13 EURO 4/5 FM 13-360 4X4 EURO 4/5 INC. D13A (2006 AND AFTER)



USE		CLIMATE
Normal service category 1, 2, 3, 4		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 400000 km/ 36 months</i>		
USE		CLIMATE
Normal service category 1, 2		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		
<i>Change every 400000 km/ 36 months</i>		
USE		CLIMATE
Normal (alternative) service categories 1, 2		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 40	SP Gear 1011	Syngear TDL 75W-90
<i>Change every 120000 km/ 12 months</i>		
USE		CLIMATE
Severe service category 1, 2		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		
<i>Change every 200000 km/ 36 months</i>		
USE		CLIMATE
Severe service category 1, 2, 3, 4		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 200000 km/ 36 months</i>		
USE		CLIMATE
Severe (alternative) service categories 1, 2		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 40	SP Gear 1011	Syngear TDL 75W-90
<i>Change every 60000 km/ 12 months</i>		
USE		CLIMATE
Extremely severe, service categories 1, 2, 3, 4		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 2500 hours</i>		

TRANSMISSION AUTOMATED I-Shift ATO2512C 12/2

VOLVO (EU) FM-13 EURO 4/5 FM 13-360 4X4 EURO 4/5 INC. D13A (2006 AND AFTER)



USE		CLIMATE
Normal service category 1, 2, 3, 4		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 400000 km/ 36 months</i>		
USE		CLIMATE
Normal service category 1, 2		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		
<i>Change every 400000 km/ 36 months</i>		
USE		CLIMATE
Normal (alternative) service categories 1, 2		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 40	SP Gear 1011	Syngear TDL 75W-90
<i>Change every 120000 km/ 12 months</i>		
USE		CLIMATE
Severe service category 1, 2		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		
<i>Change every 200000 km/ 36 months</i>		
USE		CLIMATE
Severe service category 1, 2, 3, 4		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 200000 km/ 36 months</i>		
USE		CLIMATE
Severe (alternative) service categories 1, 2		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 40	SP Gear 1011	Syngear TDL 75W-90
<i>Change every 60000 km/ 12 months</i>		
USE		CLIMATE
Extremely severe, service categories 1, 2, 3, 4		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
<i>Change every 2500 hours</i>		

VOLVO (EU) FM-13 EURO 4/5 FM 13-360 4X4 EURO 4/5 INC. D13A (2006 AND AFTER)


TRANSMISSION AUTOMATIC Powertronic VT2006PT 6/1

Capacity: 35 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Change every 200000 km/ 24 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Change every 100000 km/ 12 months*

USE	CLIMATE
Very severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Change every 50000 km/ 12 months*

USE	CLIMATE
Very severe+	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Change every 800 hours*

VOLVO (EU) FM-13 EURO 4/5 FM 13-360 4X4 EURO 4/5 INC. D13A (2006 AND AFTER)


TRANSMISSION AUTOMATIC Powertronic VT2506PT 6/1

Capacity: 35 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4036		

Change every 200000 km/ 24 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4036		

Change every 100000 km/ 12 months

USE	CLIMATE
Very severe	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4036		

Change every 50000 km/ 12 months

USE	CLIMATE
Very severe+	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4036		

Change every 800 hours

TRANSMISSION MANUAL Volvo VT2009B 9/1

Capacity: 12 liter, Capacity: 12,8 liter (+ oil cooler)

USE	CLIMATE
Normal service category 1, 2, 3, 4	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 400000 km/ 36 months

USE	CLIMATE
Normal service category 1, 2	Moderate

PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		

Change every 400000 km/ 36 months

VOLVO (EU) FM-13 EURO 4/5 FM 13-360 4X4 EURO 4/5 INC. D13A (2006 AND AFTER)



USE		CLIMATE
Normal (alternative) service categories 1, 2		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 40	SP Gear 1011	Syngear TDL 75W-90

Change every 120000 km/ 12 months

USE		CLIMATE
Severe service category 1, 2		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		

Change every 200000 km/ 36 months

USE		CLIMATE
Severe service category 1, 2, 3, 4		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 200000 km/ 36 months

USE		CLIMATE
Severe (alternative) service categories 1, 2		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 40	SP Gear 1011	Syngear TDL 75W-90

Change every 60000 km/ 12 months

USE		CLIMATE
Extremely severe, service categories 1, 2, 3, 4		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 2500 hours

TRANSMISSION MANUAL Volvo VT2214B 14/2 Capacity: 13,5 liter, Capacity: 14,3 liter (+ oil cooler)

USE		CLIMATE
Normal service category 1, 2, 3, 4		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 400000 km/ 36 months

USE		CLIMATE
Normal service category 1, 2		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		

Change every 400000 km/ 36 months

VOLVO (EU) FM-13 EURO 4/5 FM 13-360 4X4 EURO 4/5 INC. D13A (2006 AND AFTER)



USE		CLIMATE
Normal (alternative) service categories 1, 2		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 40	SP Gear 1011	Syngear TDL 75W-90

Change every 120000 km/ 12 months

USE		CLIMATE
Severe service category 1, 2		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		

Change every 200000 km/ 36 months

USE		CLIMATE
Severe service category 1, 2, 3, 4		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 200000 km/ 36 months

USE		CLIMATE
Severe (alternative) service categories 1, 2		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 40	SP Gear 1011	Syngear TDL 75W-90

Change every 60000 km/ 12 months

USE		CLIMATE
Extremely severe, service categories 1, 2, 3, 4		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 2500 hours

TRANSMISSION MANUAL Volvo VTO2214B 14/2 Capacity: 13,5 liter, Capacity: 14,3 liter (+ oil cooler)

USE		CLIMATE
Normal service category 1, 2, 3, 4		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 400000 km/ 36 months

USE		CLIMATE
Normal service category 1, 2		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		

Change every 400000 km/ 36 months

VOLVO (EU) FM-13 EURO 4/5 FM 13-360 4X4 EURO 4/5 INC. D13A (2006 AND AFTER)



USE		CLIMATE
Normal (alternative) service categories 1, 2		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 40	SP Gear 1011	Syngear TDL 75W-90

Change every 120000 km/ 12 months

USE		CLIMATE
Severe service category 1, 2		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		

Change every 200000 km/ 36 months

USE		CLIMATE
Severe service category 1, 2, 3, 4		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 200000 km/ 36 months

USE		CLIMATE
Severe (alternative) service categories 1, 2		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 40	SP Gear 1011	Syngear TDL 75W-90

Change every 60000 km/ 12 months

USE		CLIMATE
Extremely severe, service categories 1, 2, 3, 4		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 2500 hours

BOGIE LIFT		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Fluid 3013	Perlus H 15	

Change every 12 months

VOLVO (EU) FM-13 EURO 4/5 FM 13-360 4X4 EURO 4/5 INC. D13A (2006 AND AFTER)



HYDRAULIC CAB TILT SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 15		
<i>Check every 12 months</i>		

HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
<i>Check every 12 months</i>		

POWER STEERING

Capacity: 6-9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	
<i>Check every 12 months</i>		

CENTRAL LUBRICATION SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Grease EP 00/000		
<i>Change every 6 months</i>		

COOLING SYSTEM

Capacity: 44 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	
<i>Change every 500000 km/ 48 months</i>		

VOLVO (EU) FM-13 EURO 4/5 FM 13-360 4X4 EURO 4/5 INC. D13A (2006 AND AFTER)



AIRCONDITIONING COMPRESSOR

Capacity: 165 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

Capacity: 1050-1100 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.