IRISBUS CITELIS CITELIS EURO 4 RCL2B/RCL2C (2005-2012)



ENGINE Cursor 8 Capacity: 14 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP 10W-40	Armado Synth 10W-40	Armado Synth 5W-30

Change every 40000 km/ 12 months/ 4000 hours

DIFFERENTIAL REAR		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube HS GL-5 80W-140	Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140
Change every 80000 km/24 months		1

TRANSMISSION AUTOMATIC Voith D 854.5 4/1

USE

Normal

PRODUCT RECOMMENDATION 1

SP Matic 2032

Change every 90000 km/24 months

TRANSMISSION AUTOMATIC ZF Capacity: 25-30 liter	F 5HP502C 5/1	
USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032 ATF Almirol		
Change every 45000 km	'	'

TRANSMISSION AUTOMATIC ZF Capacity: 25-30 liter	6HP502C 6/1		
USE		CLIMATE	
Alternative (acceptable)		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 2032	ATF Almirol		
Change every 45000 km			

IRISBUS CITELIS CITELIS EURO 4 RCL2B/RCL2C (2005-2012)



HYDROSTATIC FAN		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
Change every 12 months	·	·

HYDRAULIC POWER STEERING ZF 8098			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 2032	ATF Almirol		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

GREASE POINTS/NIPPLES ACCESS RAMP GEARMOTOR

We are unable to give a standard recommendation for this component. Please contact our service department.

WHEEL BEARINGS GREASED			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Labora Grease	Multi Purpose Grease 3		

COOLING SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	
Change every 24 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.