

MAN TGS EURO 4 TGS 24.320 (6X2/2) EGR EURO 4 (2008-2011)



ENGINE D 2066 LF39 EGR
Capacity: 42 liter

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40

Change every 120000 km/ 12 months

DIFFERENTIAL REAR HY-1350
Capacity: 14,5 liter

USE	CLIMATE
Extended	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 500000 km/ 36 months

USE	CLIMATE
Extended, tropical climate	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 360000 km/ 36 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 320000 km/ 24 months

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

Change every 160000 km/ 24 months

USE	CLIMATE
Tropical climate	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 210000 km/ 24 months

MAN TGS EURO 4 TGS 24.320 (6X2/2) EGR EURO 4 (2008-2011)



USE		CLIMATE
Alternative (acceptable), tropical climate		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90
Change every 110000 km/ 24 months		

TRANSMISSION AUTOMATIC ZF 12AS-2130 DD (TipMatic) 12/1 Capacity: 12 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		
Change every 320000 km/ 24 months		

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear HS 75W-90
Change every 160000 km/ 12 months		

TRANSMISSION MANUAL ZF 16S-2220 16/2 Capacity: 13 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		
Change every 320000 km/ 24 months		

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear HS 75W-90
Change every 160000 km/ 12 months		

HYDRAULIC CAB TILT SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 15		

MAN TGS EURO 4 TGS 24.320 (6X2/2) EGR EURO 4 (2008-2011)



HYDRAULIC SYSTEM BOGIE LIFT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

HYDRAULIC CLUTCH + HGS (KONGSBERG) GEAR ACTUATION SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

POWER STEERING ZF Servocom Capacity: 6-7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

MAN TGS EURO 4 TGS 24.320 (6X2/2) EGR EURO 4 (2008-2011)


POWER STEERING DUAL-CIRCUIT ZF Servocom

Capacity: 15-16 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

CENTRAL LUBRICATION SYSTEM BEKA-MAX

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
HT Q9 High Grade Grease		

CENTRAL LUBRICATION SYSTEM Groeneveld

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Grease EP 0	Gear Grease EP 00/000	

CENTRAL LUBRICATION SYSTEM OIL Vogel

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40	

WHEEL BEARINGS REAR

Capacity: 120 grams (each side)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
HT Q9 High Grade Grease		

MAN TGS EURO 4 TGS 24.320 (6X2/2) EGR EURO 4 (2008-2011)

**COOLING SYSTEM**

Capacity: 52 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 500000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.