PRODUCT RECOMMENDATION

MAN TGS EURO 4 TGS 41.400 (8X4) EGR EURO 4 (2008-2011)

ENGINE D 2066 LF37 EGR
Capacity: 42 liter

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	**Armado Synth LSP Ultra 10W-40**	**Armado Synth LSP 10W-40**

Change every 120000 km/ 12 months

DIFFERENTIAL REAR LEADING MAN HPD-1382
Capacity: 13,5 liter, Capacity: 2,8 liter (each hub)

USE	CLIMATE
Extended	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1011	**Syngear TDL 75W-90**

Change every 180000 km/ 36 months

USE	CLIMATE
Extended, tropical climate	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1011	**Syngear TDL 75W-90**

Change every 120000 km/ 36 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	**Syngear TDL 75W-90**	**Gearlube GL-5 80W-90**

Change every 160000 km/ 24 months

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1
Gearlube GL-5 80W-90

Change every 90000 km/ 24 months

USE	CLIMATE
Tropical climate	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	**Syngear TDL 75W-90**	**Gearlube GL-5 80W-90**

Change every 110000 km/ 24 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

MAN TGS EURO 4 TGS 41.400 (8X4) EGR EURO 4 (2008-2011)

USE	CLIMATE
Alternative (acceptable), tropical climate	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		

Change every 60000 km/ 24 months

DIFFERENTIAL REAR TRAILING MAN HP-1352
Capacity: 12 liter, Capacity: 2,1 liter (each hub)

USE	CLIMATE
Extended	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	**Syngear TDL 75W-90**	

Change every 180000 km/ 36 months

USE	CLIMATE
Extended, tropical climate	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	**Syngear TDL 75W-90**	

Change every 120000 km/ 36 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	**Syngear TDL 75W-90**	**Gearlube GL-5 80W-90**

Change every 160000 km/ 24 months

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		

Change every 90000 km/ 12 months

USE	CLIMATE
Tropical climate	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	**Syngear TDL 75W-90**	**Gearlube GL-5 80W-90**

Change every 110000 km/ 24 months

USE	CLIMATE
Alternative (acceptable), tropical climate	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		

Change every 60000 km/ 24 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

MAN TGS EURO 4 TGS 41.400 (8X4) EGR EURO 4 (2008-2011)

TRANSMISSION MANUAL ZF 16S-2220 16/2

Capacity: 13 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Syngear MT/LD 75W-80		

Change every 320000 km/ 24 months

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
SP Gear 1011	**Syngear TDL 75W-90**	**Syngear HS 75W-90**

Change every 160000 km/ 12 months

HYDRAULIC CAB TILT SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 15		

HYDRAULIC CLUTCH + HGS (KONGSBERG) GEAR ACTUATION SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 5.1		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

MAN TGS EURO 4 TGS 41.400 (8X4) EGR EURO 4 (2008-2011)

POWER STEERING ZF Servocom
Capacity: 6-7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	**ATF Almirol**	**ATF Dexron II-D**

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	**ATF Almirol**	**ATF Dexron II-D**

POWER STEERING DUAL-CIRCUIT ZF Servocom
Capacity: 15-16 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	**ATF Almirol**	**ATF Dexron II-D**

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	**ATF Almirol**	**ATF Dexron II-D**

CENTRAL LUBRICATION SYSTEM BEKA-MAX

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
HT Q9 High Grade Grease		

CENTRAL LUBRICATION SYSTEM Groeneveld

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Grease EP 0	**Gear Grease EP 00/000**	

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

MAN TGS EURO 4 TGS 41.400 (8X4) EGR EURO 4 (2008-2011)

CENTRAL LUBRICATION SYSTEM OIL Vogel

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Armado Synth LSP Ultra 10W-40	**Armado Synth LSP 10W-40**	

COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Coolant SP 15+	**Coolant SP 12**	
Change every 500000 km/ 48 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367