

MERCEDES-BENZ (EU) LK 673 --> 679 709 (673) (1984-1996)



ENGINE OM364 (Euro 1)
Capacity: 10 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet MSP 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 10000 km/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40

Change every 10000 km/ 12 months

DIFFERENTIAL REAR
Capacity: 3,25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube GL-5 80W-90

Check every 10000 km, change every 40000 km

POWER TAKE OFF
Capacity: 1,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
ATF-A		

Check every 10000 km, change every 40000 km

MERCEDES-BENZ (EU) LK 673 --> 679 709 (673) (1984-1996)

**TRANSMISSION AUTOMATIC 4/1**

Capacity: 10 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4026	SP Matic 2032	

Check every 10000 km, change every 40000 km

USE		CLIMATE
Special circumstances		Moderate
PRODUCT RECOMMENDATION 1		
ATF-A		

Check every 10000 km, change every 40000 km

TRANSMISSION AUTOMATIC Allison AT 542 4/1

Capacity: 12,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF-A		

Check every 10000 km, change every 40000 km

TRANSMISSION MANUAL 5/1

Capacity: 3,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF-A		

Check every 10000 km, change every 40000 km

TRANSMISSION MANUAL G3/45 6/1

Capacity: 4,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Syngear HS 75W-90	Gearlube GL-4 80W	Gearlube GL-4 80W-90

Check every 10000 km, change every 40000 km

MERCEDES-BENZ (EU) LK 673 --> 679 709 (673) (1984-1996)



HYDRAULIC CLUTCH SYSTEM

Capacity: 0,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-S DOT 4*Change every 24 months*

POWER STEERING

Capacity: 2,2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

PRODUCT RECOMMENDATION 2

SP Matic 2032

PRODUCT RECOMMENDATION 3

ATF-A

GREASE POINTS/NIPPLES CLUTCH RELEASE BEARING

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

MoS2 Grease EP 2*Check every 60000 km*

GREASE POINTS/NIPPLES OTHERS

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 2

MP Lithep Grease EP 2*Check every 10000 km*

GREASE POINTS/NIPPLES SLIDING JOINTS

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

MoS2 Grease EP 2*Check every 40000 km*

MERCEDES-BENZ (EU) LK 673 --> 679 709 (673) (1984-1996)



GREASE POINTS/NIPPLES WHEEL BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

Change every 12 months

COOLING SYSTEM

Capacity: 20 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 11	

Change every 36 months

OIL BATH AIR CLEANER

Capacity: 1,7 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet MSP 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 20000 km

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 5W-30	Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40

Change every 20000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.