HARLEY-DAVIDSON SOFTAIL FLS/FXS FXCWC ROCKER C JK (2008-2010)



| USE Normal (alternative) Moderate PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50 Change every 8000 km USE CLIMATE Normal (preferred) Mediterranean PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50 Change every 8000 km USE CLIMATE Mediterranean PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50 Change every 8000 km USE CLIMATE Mediterranean PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50 | |
|---|--|
| PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50 Change every 8000 km USE CLIMATE Normal (preferred) Mediterranean PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50 Change every 8000 km USE CLIMATE Initial service Mediterranean | |
| Change every 8000 km USE CLIMATE Normal (preferred) Mediterranean PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50 Change every 8000 km USE CLIMATE Initial service Mediterranean | |
| Change every 8000 km USE CLIMATE Normal (preferred) Mediterranean PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50 Change every 8000 km USE CLIMATE Initial service Mediterranean | |
| USE Normal (preferred) PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50 Change every 8000 km USE Initial service PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 1 | |
| Normal (preferred) PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50 Change every 8000 km USE Initial service PRODUCT RECOMMENDATION 1 Mediterranean Mediterranean | |
| PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50 Change every 8000 km USE CLIMATE Initial service Mediterranean PRODUCT RECOMMENDATION 1 | |
| Bi-Turbo 20W-50 Change every 8000 km USE CLIMATE Initial service Mediterranean PRODUCT RECOMMENDATION 1 | |
| Change every 8000 km USE CLIMATE Initial service Mediterranean PRODUCT RECOMMENDATION 1 | |
| USE CLIMATE Initial service Mediterranean PRODUCT RECOMMENDATION 1 | |
| Initial service Mediterranean PRODUCT RECOMMENDATION 1 | |
| PRODUCT RECOMMENDATION 1 | |
| | |
| Bi-Turbo 20W-50 | |
| | |
| Change every 1600 km | |
| USE | |
| Acceptable Mediterranean | |
| PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 | |
| Bi-Turbo 20W-50 | |
| | |
| PRIMARY CHAINDRIVE | |
| Capacity: 0,95 liter | |
| USE CLIMATE | |
| Normal Moderate | |
| PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50 | |
| | |
| Change every 16000 km | |
| Initial service CLIMATE Moderate | |
| | |
| PRODUCT RECOMMENDATION 1 Bi-Turbo 20W-50 | |
| | |
| Change every 1600 km | |
| | |

HARLEY-DAVIDSON SOFTAIL FLS/FXS FXCWC ROCKER C JK (2008-2010)



| TRANSMISSION 6 Capacity: 0,95 liter | |
|-------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Bi-Turbo 20W-50 | |
| Change every 32000 km | |
| USE | CLIMATE |
| Initial service | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Bi-Turbo 20W-50 | |
| Bi-1 u100 2000-30 | |

| HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.) | | | | |
|---|--------------------------|----------|--|--|
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | | | |
| 01 1 00001 1 | | | | |

Check every 8000 km, change every 24 months

FRONT FORK

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.