

# YAMAHA (USA) XV VIRAGO XV 535 VIRAGO (1995-2000)



## ENGINE/TRANSMISSION

Capacity: 3,2 liter (Dry fill), Capacity: 2,8 liter (Service fill), Filter capacity: 0,2 liter

## USE

Normal

## CLIMATE

Mediterranean

## PRODUCT RECOMMENDATION 1

**Expulsa 10W-40***Change every 3800 miles/ 6 months*

## USE

Initial service

## CLIMATE

Mediterranean

## PRODUCT RECOMMENDATION 1

**Expulsa 10W-40***Change every 600 miles/ 1 months*

## FINAL DRIVES

Capacity: 0,2 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**SP Gear 5015**

## PRODUCT RECOMMENDATION 2

**Gearlube GL-4 80W***Change every 16000 miles/ 24 months*

## HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

## PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4**

## PRODUCT RECOMMENDATION 3

**Drauliquid DOT 3***Change every 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.