APRILIA ATLANTIC ATLANTIC 125 (2002-2004)



ENGINE Capacity: 1,1 liter, Capacity: 1,15 liter (Overhaul capacity), Filter capacity: 0,1 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Expulsa RR 5W-40			
Check every 3000 km, change every 6000 km			
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1			
Expulsa RR 5W-40			
Change every 1000 km			

FINAL REDUCTION Capacity: 0,25 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear 75W-90	

Check every 6000 km, change every 24000 km

0/ / / / / / / / / / / / / / / / / / /		•
SP Gear 1011	Syngear 75W-90	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Initial service		Moderate
USE		CLIMATE

Change every 1000 km

HYDRAULIC BRAKE SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
	1	1	

Check every 6000 km/8 months, change every 24 months

APRILIA ATLANTIC ATLANTIC 125 (2002-2004)



GREASE POINTS/NIPPLES		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		
Charles average 6000 kms/ 0 magnitude		

Check every 6000 km/ 8 months

COOLING SYSTEM Capacity: 1,2 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 11	

Check every 2000 km, change every 16 months

FRONT FORK Capacity: 0,15 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Fork Oil RR 5	Perlus H 46	
Check every 5000 km/9 menths, chenge every 12000 km/16 menths		

Check every 6000 km/8 months, change every 12000 km/16 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.