APRILIA ATLANTIC ATLANTIC 500 SPRINT (2006-2010)



| ENGINE | | |
|--|------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Expulsa RR 5W-40 | | |
| Check every 5000 km, change every 1000 | 0 km | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Expulsa RR 5W-40 | | |
| Change every 1000 km | | |

| FINAL REDUCTION Capacity: 0,25 liter | | |
|---|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| SP Gear 1011 | Syngear 75W-90 | |
| Check every 10000 km/ 12 months | | |

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| SP Gear 1011 | Syngear 75W-90 | |
| Change even 1000 km | | |

Change every 1000 km

| HYDRAULIC BRAKE SYSTEM | | |
|------------------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | |
| Check every 10000 km, change every | 24 months | |

| GREASE POINTS/NIPPLES | | | |
|---------------------------------|--|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | | | |
| MoS2 Grease EP 2 | | | |
| Check eveny 10000 km/ 12 months | | | |

Check every 10000 km/ 12 months

APRILIA ATLANTIC ATLANTIC 500 SPRINT (2006 - 2010)



| COOLING SYSTEM Capacity: 1,5 liter | | | |
|---------------------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Coolant -38 Organic NF | Coolant -26 | | |
| Check every 24 months | | | |
| USE | | CLIMATE | |
| Initial service | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Coolant -38 Organic NF | Coolant -26 | | |
| Check every 1000 km | | | |

FRONT FORK USE CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Fork Oil RR 5 Perlus H 46

Check every 10000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.