

# APRILIA LEONARDO LEONARDO 250 (2006-2008)



## ENGINE

Capacity: 1,4 liter (Dry fill), Capacity: 1,2 liter (Service fill)

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-40***Check every 1000 km, change every 6000 km/ 12 months*

### USE

Initial service

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-40***Change every 1000 km*

## FINAL REDUCTION

Capacity: 0,25 liter

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**SP Gear 1011**

### PRODUCT RECOMMENDATION 2

**Syngear 75W-90***Check every 6000 km/ 12 months, change every 12000 km/ 24 months*

### USE

Initial service

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**SP Gear 1011**

### PRODUCT RECOMMENDATION 2

**Syngear 75W-90***Change every 1000 km*

## HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Drauliquid DOT 5.1**

### PRODUCT RECOMMENDATION 2

**Drauliquid-LV Super DOT 4**

### PRODUCT RECOMMENDATION 3

**Drauliquid-S DOT 4***Check every 6000 km/ 12 months, change every 24 months*

# APRILIA LEONARDO LEONARDO 250 (2006-2008)



## COOLING SYSTEM

Capacity: 1,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Check every 2000 km, change every 24 months*

## FRONT FORK

Capacity: 148 CM3 (each side)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus H 32</b>		

*Check every 12000 km*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*