APRILIA RXV / SXV RXV / SXV 550 (2005-2017)



ENGINE

Capacity: 1,3 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION 5

We are unable to give a standard recommendation for this component. Please contact our service department.

| HYDRAULIC BRAKE SYSTEM | | | |
|--|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | | |
| Check every 3000 km, change every 12 r | nonths | · | |
| USE | | CLIMATE | |
| Severe | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | | |
| Check every 15 hours, change every 12 months | | | |
| USE | | CLIMATE | |
| First change only | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | | |
| Check every 500 km | | | |
| USE | | CLIMATE | |
| Severe, first change only | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | | |
| Check every 3 hours | | | |

APRILIA RXV / SXV RXV / SXV 550 (2005-2017)



| COOLING SYSTEM Capacity: 1,1 liter | | |
|------------------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 11 | | |
| Check every 3000 km | | |
| USE | | CLIMATE |
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 11 | | |
| Check every 15 hours | | |
| USE | | CLIMATE |
| First change only | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 11 | | |
| Check every 500 km | | |
| USE | | CLIMATE |
| Severe, first change only | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 11 | | |
| Check every 3 hours | | |
| | | |
| FRONT FORK | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Fork Oil RR 10 | Perlus H 32 | |
| Change every 9000 km | | |
| USE | | CLIMATE |
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Fork Oil RR 10 | Perlus H 32 | |
| Change every 45 hours | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.