## ARCTIC CAT PROWLER SERIES PROWLER XT 1000 (2015-2016)



## ENGINE H2

Capacity: 1,9 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

| <b>DIFFERENTIAL FRONT</b> (4x4)<br>Capacity: 0,28 liter |                             |          |
|---|-----------------------------|----------|
| USE   |                             | CLIMATE  |
| Normal  |                             | Moderate |
| PRODUCT RECOMMENDATION 1                                | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90                                    | Unigear HS GL-3/GL-5 80W-90 |          |

Check every 300 miles, change every 2000 miles/ 24 months

| USE                      |                             | CLIMATE  |
|--------------------------|-----------------------------|----------|
| Initial service          |                             | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90     | Unigear HS GL-3/GL-5 80W-90 |          |
|                          |                             |          |

Change every 100 miles

| DIFFERENTIAL REAR<br>Capacity: 0,25 liter |                             |          |
|---|-----------------------------|----------|
| USE                                       |                             | CLIMATE  |
| Normal                                    |                             | Moderate |
| PRODUCT RECOMMENDATION 1                  | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90                      | Unigear HS GL-3/GL-5 80W-90 |          |

Check every 300 miles, change every 2000 miles/24 months

| USE                      |                             | CLIMATE  |
|--------------------------|-----------------------------|----------|
| Initial service          |                             | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90     | Unigear HS GL-3/GL-5 80W-90 |          |

Change every 100 miles

| HYDRAULIC BRAKE SYSTEM<br>Capacity: 0-0 liter (Between min and max.) |                          |          |
|--|--------------------------|----------|
| USE  |                          | CLIMATE  |
| Normal   |                          | Moderate |
| PRODUCT RECOMMENDATION 1   | PRODUCT RECOMMENDATION 2 |          |
| Drauliquid-LV Super DOT 4  | Drauliquid-S DOT 4       |          |

Change every 24 months

## ARCTIC CAT PROWLER SERIES PROWLER XT 1000 (2015-2016)



| COOLING SYSTEM<br>Capacity: 3,3 liter |          |
|---------------------------------------|----------|
| USE                                   | CLIMATE  |
| Normal                                | Moderate |
| PRODUCT RECOMMENDATION 1              |          |
| Coolant -38 Organic NF                |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.