

# ARCTIC CAT PROWLER SERIES PROWLER

## XTX 700 H1 EFI (2009-2011)

**ENGINE**

Capacity: 1,9 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Expulsa RR 5W-50***Change every 3 months/ 300 miles***USE**

Initial service

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Expulsa RR 5W-50***Change every 100 km***DIFFERENTIAL FRONT (4x4)**

Capacity: 275 CM3

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gearlube LS 80W-90***Change every 48 months***DIFFERENTIAL REAR**

Capacity: 250 CM3

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gearlube LS 80W-90***Change every 48 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Drauliquid-LV Super DOT 4****PRODUCT RECOMMENDATION 2****Drauliquid-S DOT 4***Change every 24 months*

# ARCTIC CAT PROWLER SERIES PROWLER XTX 700 H1 EFI (2009-2011)

**COOLING SYSTEM**

Capacity: 2,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*