## **ARCTIC CAT WILDCAT WILDCAT 1000**

(2011-2012)



ENGINE H2 Capacity: 2,8 liter (Dry fill), Capacity: 2,3 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Expulsa RR 5W-50				
Change every 3 months/ 300 miles				
USE		CLIMATE		
Initial service		Moderate		
PRODUCT RECOMMENDATION 1				
Expulsa RR 5W-50				
Change every 100 km				

<b>DIFFERENTIAL FRONT</b> (4x4) Capacity: 200 CM3	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 48 months	

DIFFERENTIAL REAR Capacity: 175 CM3	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 48 months	·

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			
Change every 24 months				

## **ARCTIC CAT WILDCAT WILDCAT 1000**

(2011-2012)



COOLING SYSTEM Capacity: 3,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.