

# ARGO FRONTIER 8X8 FRONTIER 650 (2007 AND AFTER)



**ENGINE** Briggs & Stratton Vanguard  
Capacity: 1,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-40**

*Change every 50 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-40**

*Change every 8 hours*

**TRANSMISSION** 2/1  
Capacity: 1,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Gear 1011**

PRODUCT RECOMMENDATION 2

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 3

**Unigear HS GL-3/GL-5 80W-90**

*Check every 50 hours, change every 100 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**SP Gear 1011**

PRODUCT RECOMMENDATION 2

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 3

**Unigear HS GL-3/GL-5 80W-90**

*Check every 2 hours, change every 20 hours*

## HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*