BETA REV REV 3 (200CC) (2007-2008)



ENGINE Beta Capacity: 0-0 liter (Between min and max.)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Tornado				

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			
Charles years 4000 km/ 40 having always a years 2000 km/ 400 having				

Check every 1000 km/ 40 hours, change every 3000 km/ 120 hours

HYDRAULIC CLUTCH SYSTEM Capacity: 0-0 liter (Between min and max.)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			

Check every 1000 km/ 40 hours, change every 3000 km/ 120 hours

COOLING SYSTEM Capacity: 0,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Check every 1000 km/ 40 hours, change every 3000 km/ 12	20 hours

Change every 1000 km/40 hours

BETA REV REV 3 (200CC) (2007-2008)



FRONT FORK LEFT Capacity: 0,35 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Fork Oil RR 5			
Change every 8000 km/ 320 hours			
USE		CLIMATE	
First change only		Moderate	
PRODUCT RECOMMENDATION 1			
Fork Oil RR 5			
Change every 1000 km/ 40 hours			
FRONT FORK RIGHT Capacity: 0,37 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Fork Oil RR 5			
Change every 8000 km/ 320 hours			
USE		CLIMATE	
First change only		Moderate	
PRODUCT RECOMMENDATION 1			
Fork Oil RR 5			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.