## BRP CAN-AM DS DS 450 (2010-2013)



USE	CLIMATE
Normal	Tropical
PRODUCT RECOMMENDATION 1	
Expulsa RR 5W-50	
Change every 1250 km/ 25 hours	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Expulsa RR 5W-40	
Change every 1250 km/ 25 hours	
USE	CLIMATE
Normal	Arctic
PRODUCT RECOMMENDATION 1	
Helar 0W-40	
Change every 1250 km/ 25 hours	
USE	CLIMATE — · ·
Initial service	Tropical
PRODUCT RECOMMENDATION 1	
Expulsa RR 5W-50	
Change every 5 hours	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Expulsa RR 5W-40	
Change every 5 hours	
USE	CLIMATE
Initial service	Arctic
PRODUCT RECOMMENDATION 1  Helar 0W-40	
I ICIAI VYY-4V	

## BRP CAN-AM DS DS 450 (2010-2013)



HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and m	aax.)		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		

Change every 10000 km/24 months/200 hours

COOLING SYSTEM Capacity: 1,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Change every 10000 km/24 months/200 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.