

BRP CAN-AM DS DS 70 (2011-2013)**ENGINE**

Capacity: 0,95-1,1 liter

USE

Normal

CLIMATE

Tropical

PRODUCT RECOMMENDATION 1**Expulsa RR 5W-50***Change every 3 months/ 40 hours***USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Expulsa RR 5W-40***Change every 3 months/ 40 hours***USE**

Normal

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1**Helar 0W-40***Change every 3 months/ 40 hours***USE**

Initial service

CLIMATE

Tropical

PRODUCT RECOMMENDATION 1**Expulsa RR 5W-50***Change every 200 km/ 10 hours/ 30 days***USE**

Initial service

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Expulsa RR 5W-40***Change every 200 km/ 10 hours/ 30 days***USE**

Initial service

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1**Helar 0W-40***Change every 200 km/ 10 hours/ 30 days*

BRP CAN-AM DS DS 70 (2011-2013)**FINAL DRIVES**

Capacity: 0,17 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1011****PRODUCT RECOMMENDATION 2****Syngear 75W-90***Change every 24 months/ 200 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.