

BRP CAN-AM OUTLANDER OUTLANDER 500 EFI (2007-2009)



ENGINE		
Capacity: 2 liter		
USE	CLIMATE	
Normal	Tropical	
PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-50		
<i>Change every 3000 km/ 12 months/ 100 hours</i>		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-40		
<i>Change every 3000 km/ 12 months/ 100 hours</i>		
USE	CLIMATE	
Normal	Arctic	
PRODUCT RECOMMENDATION 1		
Helar 0W-40		
<i>Change every 3000 km/ 12 months/ 100 hours</i>		
USE	CLIMATE	
Initial service	Tropical	
PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-50		
<i>Change every 300 km/ 10 hours</i>		
USE	CLIMATE	
Initial service	Moderate	
PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-40		
<i>Change every 300 km/ 10 hours</i>		
USE	CLIMATE	
Initial service	Arctic	
PRODUCT RECOMMENDATION 1		
Helar 0W-40		
<i>Change every 300 km/ 10 hours</i>		

BRP CAN-AM OUTLANDER OUTLANDER 500 EFI (2007-2009)



DIFFERENTIAL FRONT

Capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear 75W-90	

Change every 6000 km/ 24 months/ 200 hours

DIFFERENTIAL REAR

Capacity: 0,25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

Change every 6000 km/ 24 months/ 200 hours

GEARBOX

Capacity: 0,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

Change every 6000 km/ 24 months/ 200 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

Change every 300 km/ 10 hours

HYDRAULIC BRAKE SYSTEM

Capacity: 0,18 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 6000 km/ 24 months/ 200 hours

BRP CAN-AM OUTLANDER OUTLANDER 500 EFI (2007-2009)



COOLING SYSTEM

Capacity: 2,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Change every 6000 km/ 24 months/ 200 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 300 km/ 10 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.