

# BRP CAN-AM OUTLANDER OUTLANDER 650 EFI (2012-2013)



**ENGINE** Rotax 660  
Capacity: 2,2 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Tropical |

PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-50**

*Change every 3000 km/ 12 months/ 100 hours*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-40**

*Change every 3000 km/ 12 months/ 100 hours*

| USE    | CLIMATE |
|--------|---------|
| Normal | Arctic  |

PRODUCT RECOMMENDATION 1

**Helar 0W-40**

*Change every 3000 km/ 12 months/ 100 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Tropical |

PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-50**

*Change every 300 km/ 10 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-40**

*Change every 300 km/ 10 hours*

| USE             | CLIMATE |
|-----------------|---------|
| Initial service | Arctic  |

PRODUCT RECOMMENDATION 1

**Helar 0W-40**

*Change every 300 km/ 10 hours*

# BRP CAN-AM OUTLANDER OUTLANDER 650 EFI (2012-2013)

**DIFFERENTIAL FRONT**

Capacity: 0,5 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>SP Gear 1011</b>      | <b>Syngear 75W-90</b>    |          |

Change every 6000 km/ 24 months/ 200 hours

**DIFFERENTIAL REAR**

Capacity: 0,3 liter

| USE                            |  | CLIMATE  |
|--------------------------------|--|----------|
| Normal                         |  | Moderate |
| PRODUCT RECOMMENDATION 1       |  |          |
| <b>Gearlube Racing 75W-140</b> |  |          |

Change every 6000 km/ 24 months/ 200 hours

**GEARBOX**

Capacity: 0,4 liter

| USE                            |  | CLIMATE  |
|--------------------------------|--|----------|
| Normal                         |  | Moderate |
| PRODUCT RECOMMENDATION 1       |  |          |
| <b>Gearlube Racing 75W-140</b> |  |          |

Change every 6000 km/ 24 months/ 200 hours

| USE                            |  | CLIMATE  |
|--------------------------------|--|----------|
| Initial service                |  | Moderate |
| PRODUCT RECOMMENDATION 1       |  |          |
| <b>Gearlube Racing 75W-140</b> |  |          |

Change every 300 km/ 10 hours

**HYDRAULIC BRAKE SYSTEM**

Capacity: 0,18 liter

| USE                              |                           | CLIMATE  |
|----------------------------------|---------------------------|----------|
| Normal                           |                           | Moderate |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  |          |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |          |

Change every 6000 km/ 24 months/ 200 hours

# BRP CAN-AM OUTLANDER OUTLANDER 650 EFI (2012-2013)

**COOLING SYSTEM**

Capacity: 2,5 liter

| USE                      |                          | CLIMATE                       |
|--------------------------|--------------------------|-------------------------------|
| Normal                   |                          | Moderate                      |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3      |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     | <b>Coolant -38 Organic NF</b> |

*Change every 6000 km/ 24 months/ 200 hours*

| USE                      |                          | CLIMATE                       |
|--------------------------|--------------------------|-------------------------------|
| Initial service          |                          | Moderate                      |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3      |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     | <b>Coolant -38 Organic NF</b> |

*Check every 300 km/ 10 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*