## PRODUCT RECOMMENDATION

## BUELL XB XB9SX LIGHTNING (2003-2010)



PRODUCT RECOMMENDATION 1 Bi-Turbo 15W-40	PRODUCT RECOMMENDATION 2 Bi-Turbo 20W-50		
Acceptable		Mediterranean	
JSE		CLIMATE	
Change every 1600 km		I	
Bi-Turbo 20W-50			
PRODUCT RECOMMENDATION 1			
nitial service		Mediterranean	
JSE		CLIMATE	
Change every 8000 km/ 12 months	1	1	
Bi-Turbo 20W-50			
PRODUCT RECOMMENDATION 1			
Normal (preferred)		Mediterranean	
JSE		CLIMATE	
Change every 8000 km/ 12 months	1	1	
Bi-Turbo 20W-50			
PRODUCT RECOMMENDATION 1			
Normal (alternative)		Moderate	
JSE		CLIMATE	

Capacity: 0,95 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Bi-Turbo 20W-50	
Change every 16000 km	*

use Initial service		climate Moderate
Bi-Turbo 20W-50		
Change every 1600 km		

## BUELL XB XB9SX LIGHTNING (2003-2010)



HYDRAULIC BRAKE SYSTEM Capacity: 0,35 liter					
USE		CLIMATE			
Normal		Moderate			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2				
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4				
Check every 8000 km/ 12 months, change every 24 months					
USE		CLIMATE			
Initial service		Moderate			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2				
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4				
Check every 1600 km					

## FRONT FORK

Capacity: 0,47 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.