

# CFMOTO CF 600 4X4 CF 600-5 (2013 AND AFTER)



## ENGINE/TRANSMISSION

Capacity: 2,3 liter, Filter capacity: 0,1 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Expulsa RR 10W-40***Change every 1000 km*

## USE

Initial service

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Expulsa RR 10W-40***Change every 250 km*

## DIFFERENTIAL REAR

Capacity: 0,33 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Expulsa RR 10W-40***Change every 12 months*

## HUB REDUCTIONS REAR

Capacity: 0,3 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Expulsa RR 10W-40***Change every 12 months*

## HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

## PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4**

## PRODUCT RECOMMENDATION 3

**Drauliquid DOT 3***Change every 24 months*

# CFMOTO CF 600 4X4 CF 600-5 (2013 AND AFTER)

**COOLING SYSTEM**

Capacity: 2,9 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Coolant -38 Organic NF****PRODUCT RECOMMENDATION 2****Coolant -26***Check every 1000 km*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*