

# CFMOTO CF 625 4X4 CF 625(-3) 4X4 TERRACROSS (2013 AND AFTER)



## ENGINE/TRANSMISSION

Capacity: 2,8 liter (Dry fill), Capacity: 2,5 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Expulsa RR 5W-50</b>	<b>Expulsa RR 15W-50</b>	<b>Expulsa RR 5W-40</b>

*Change every 1000 km/ 100 hours*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Expulsa RR 5W-50</b>	<b>Expulsa RR 15W-50</b>	<b>Expulsa RR 5W-40</b>

*Change every 250 km/ 20 hours*

## DIFFERENTIAL FRONT

Capacity: 0,33 liter (Dry fill), Capacity: 0,28 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Expulsa RR 10W-40</b>	<b>HDX 15W-40</b>	<b>Gearlube GL-4 80W-90</b>

*Check every 400 km/ 1 months/ 25 hours, change every 12 months*

## DIFFERENTIAL REAR

Capacity: 0,3 liter (Dry fill), Capacity: 0,25 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Expulsa RR 10W-40</b>	<b>HDX 15W-40</b>	<b>Gearlube GL-4 80W-90</b>

*Check every 400 km/ 1 months/ 25 hours, change every 12 months*

## HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	<b>Drauliquid DOT 3</b>

*Change every 3200 km/ 24 months/ 200 hours*

# CFMOTO CF 625 4X4 CF 625(-3) 4X4 TERRACROSS (2013 AND AFTER)

**COOLING SYSTEM**

Capacity: 2,7 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Coolant SP 12 EVO***Check every 12 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*