

CHATENET CH30 CH30 LGW 523 MPI (2010-2017)

**ENGINE** Lombardini LGW523

Capacity: 1,3 liter (Service fill), Filter capacity: 0,1 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Expulsa RR 5W-40*Check every 2500 km, change every 10000 km/ 12 months*

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

Expulsa RR 5W-40*Change every 1000 km***FINAL GEAR FRONT 1/1**

Capacity: 0,8 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Gearlube GL-4 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Change every 10000 km/ 24 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Change every 30000 km/ 36 months***COOLING SYSTEM**

Capacity: 4 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26*Check every 2500 km, change every 50000 km/ 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.