DUCATI 996 996 BIPOSTO/MONOPOSTO

(1998-2002)



| ENGINE/TRANSMISSION Capacity: 3,8 liter | | |
|---|--------------------------|---------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Expulsa RR 15W-50 | Bi-Turbo 20W-50 | |

Check every 1000 km, change every 10000 km

| HYDRAULIC BRAKE SYSTEM | | | |
|---------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | | |
| | | | |

Check every 1000 km, change every 20000 km

| HYDRAULIC CLUTCH SYSTEM | | | |
|---------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | | |
| | | | |

Check every 1000 km, change every 20000 km

| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |
|--------------------------|--------------------------|--------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Normal | | Moderate |
| USE | | CLIMATE |
| GREASE POINTS/NIPPLES | | |

Check every 3000 km, change every 10000 km/ 12 months

| COOLING SYSTEM Capacity: 3,5 liter | | |
|------------------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |
| Check every 1000 km, change every | 20000 km | · |

DUCATI 996 996 BIPOSTO/MONOPOSTO

(1998-2002)



| FRONT FORK Capacity: 0,48 liter | | |
|------------------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| ATF Dexron II-D | Fork Oil RR 5 | |
| Change every 20000 km | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.