DUCATI DIAVEL DIAVEL 1200 (2014-2015)



	CLIMATE	
	Mediterranean	
PRODUCT RECOMMENDATION 2		
Expulsa RR 10W-40		
		Mediterranean PRODUCT RECOMMENDATION 2

Change every 15000 km/ 12 months

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Expulsa RR 15W-50	Expulsa RR 10W-40	

Change every 1000 km

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max	.)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 15000 km/ 12 months, change every 36 months

HYDRAULIC CLUTCH SYSTEM Capacity: 0-0 liter (Between min and m	ax.)		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
		•	

Check every 15000 km/ 12 months, change every 36 months

COOLING SYSTEM Capacity: 2,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	
Check every 15000 km/ 12 months, change every 45000 km/ 48 months		

DUCATI DIAVEL DIAVEL 1200 (2014-2015)



FRONT FORK Capacity: 720 CM3 (each side)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
ATF Dexron II-D	Fork Oil RR 5	
Change every 30000 km		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.