PRODUCT RECOMMENDATION

# DUCATI HYPERMOTARD 1100 HYPERMOTARD (2008-2009)

## ENGINE/TRANSMISSION
Capacity: 3,7 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| **Expulsa RR 15W-50** | | |

*Change every 12000 km/ 12 months*

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Expulsa RR 10W-40** | | |

*Change every 12000 km/ 12 months*

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| **Expulsa RR 15W-50** | | |

*Change every 1000 km/ 6 months*

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Expulsa RR 10W-40** | | |

*Change every 1000 km/ 6 months*

## HYDRAULIC BRAKE SYSTEM
Capacity: 0-0 liter (Between min and max.)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **Drauliquid-LV Super DOT 4** | **Drauliquid-S DOT 4** | |

*Check every 12000 km/ 12 months, change every 36000 km/ 36 months*

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **Drauliquid-LV Super DOT 4** | **Drauliquid-S DOT 4** | |

*Check every 1000 km/ 6 months*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# DUCATI HYPERMOTARD 1100 HYPERMOTARD (2008-2009)

## HYDRAULIC CLUTCH SYSTEM
Capacity: 0-0 liter (Between min and max.)

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Drauliquid-LV Super DOT 4** | **Drauliquid-S DOT 4** | |

*Check every 12000 km/ 12 months, change every 36000 km/ 36 months*

| USE | CLIMATE |
|---|---|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Drauliquid-LV Super DOT 4** | **Drauliquid-S DOT 4** | |

*Check every 1000 km/ 6 months*

## GREASE POINTS/NIPPLES

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Labora Grease** | **Q5 MP Calcep Grease EP 2** | **MP Lithep Grease EP 2** |

*Change every 12000 km/ 12 months*

## FRONT FORK
Capacity: 690 CM3

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **ATF Dexron II-D** | **Fork Oil RR 5** | |

*Check every 12000 km/ 12 months, change every 36000 km/ 36 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367