FANTIC MOTOR TX CABALLERO CABALLERO 200 (2011-2015)



ENGINE/TRANSMISSION Capacity: 1 liter		
USE	CLIMATE	
Normal	Moder	rate
PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-50		
Change every 3000 km/ 12 months		
USE	CLIMATE	
Initial service	Mode	rate
PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-50		
Change every 1000 km		
HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max		

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 5.1	
Change every 24 months	

COOLING SYSTEM Capacity: 0-0 liter (Between min and max.)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Coolant -38 Organic NF	Coolant -26			
Change every 2000 km				

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.