FANTIC MOTOR TZ TZ 300 (2011-2017)



ENGINE		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Tornado	Scoosynth	Maestrol

TRANSMISSION MANUAL 6 Capacity: 0,9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Expulsa RR 5W-50	
Expulsa RR 5W-50	

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
Drauliquid DOT 5.1			
Change every 24 months	·		

COOLING SYSTEM Capacity: 0-0 liter (Between min and max.)				
use Normal		CLIMATE		
		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Coolant -38 Organic NF	Coolant -26			

FRONT FORK Capacity: 110 mm (measured compressed, without spring)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Perlus H 32				
Change every 12 months	•			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.