PRODUCT RECOMMENDATION

GAS GAS EC EC 250 F (2012-2013)



| ENGINE/TRANSMISSION Capacity: 1,3 liter | | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Expulsa RR 15W-50 | Expulsa RR 10W-40 | Expulsa 10W-40 |
| Change every 30 hours | | I |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Expulsa RR 5W-40 | | |
| Change every 30 hours | · · | |
| USE | | CLIMATE |
| Initial service | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Expulsa RR 15W-50 | Expulsa RR 10W-40 | Expulsa 10W-40 |
| Change every 5 hours | · · | · · · |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Expulsa RR 5W-40 | | |
| Change every 5 hours | · · · | |
| | | |
| HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and | max.) | |
| USE | | CLIMATE |
| Normal | | Moderate |

| | 1 | |
|---------------------------|--------------------------|--------------------------|
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | Drauliquid DOT 3 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Normal | | Moderate |

Change every 24 months

HYDRAULIC CLUTCH SYSTEM Capacity: 0-0 liter (Between min and max.)

We are unable to give a standard recommendation for this component. Please contact our service department.

GAS GAS EC EC 250 F (2012-2013)



| COOLING SYSTEM | | |
|--------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |

Change every 24 months

| FRONT FORK Capacity: 320 CM3 | |
|---------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Fork Oil RR 5 | |
| Check every 60 hours | • |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.