HARLEY-DAVIDSON DYNA FLD/FXD FXRT SPORT GLIDE 1340 (1984-1992)



USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1				
Bi-Turbo 20W-50				
Check every 2500 km, change every 5000 km				
USE		CLIMATE		
Acceptable		Mediterranean		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Bi-Turbo 15W-40	Bi-Turbo 20W-50			
USE		CLIMATE		
Acceptable		Cold		
PRODUCT RECOMMENDATION 1				
Emperol 10W-40				

PRIMARY CHAINDRIVE Capacity: 0,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Expulsa RR 10W-40	Expulsa 10W-40	
Check every 2500 km, change ever	ry 5000 km	

TRANSMISSION 5		
Capacity: 0,6 liter		

USE CLIMATE
Normal Moderate

PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2

Gearlube GL-4 80W-90 Unigear HS GL-3/GL-5 80W-90

Check every 2500 km, change every 5000 km

HYDRAULIC BRAKE SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

HARLEY-DAVIDSON DYNA FLD/FXD FXRT SPORT GLIDE 1340 (1984-1992)



FRONT FORK Capacity: 0,79 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 46	
Change every 10000 km/ 12 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.