

HARLEY-DAVIDSON SOFTAIL FLS/FXS FLSTSC/I SOFTAIL SPRINGER CLASSIC (2005-2005)



ENGINE Twin Cam 88B
Capacity: 3,3 liter

USE	CLIMATE
Normal (alternative)	Moderate

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Change every 8000 km*

USE	CLIMATE
Normal (preferred)	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Change every 8000 km*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Change every 1600 km*

USE	CLIMATE
Acceptable	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 15W-40

PRODUCT RECOMMENDATION 2

Bi-Turbo 20W-50

USE	CLIMATE
Acceptable	Cold

PRODUCT RECOMMENDATION 1

Emperol 10W-40

PRIMARY CHAINDRIVE

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Change every 16000 km*

HARLEY-DAVIDSON SOFTAIL FLS/FXS FLSTSC/I SOFTAIL SPRINGER CLASSIC (2005-2005)

**TRANSMISSION 5**

Capacity: 0,59-0,71 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Change every 32000 km*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Change every 800 km***HYDRAULIC BRAKE SYSTEM**

Capacity: 0,35 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.